


TRIA C6B-CFLH

Intel® Core™ 8th Generation

125 x 95



35 / 55W

0-+60

COM 
Express



Highlights

- Intel® Core™ i7-8850H (six-core, 2.6/4.3GHz, 45/35W cTDP),
- Intel® Core™ i5-8400H (quad-core, 2.5/4.2GHz, 45/35W cTDP)
- Intel® Core™ i3-8100H (quad-core, 3.0GHz, 45/35W cTDP)
- Intel® Xeon® E-2176M (six-core, 2.7/4.4GHz, 45/35W cTDP),
- Intel® UHD Graphics
- Intel® chipsets QM370 or CM246
- Up to 32GB DDR4-2666 SDRAM, dual channel (ECC optionally supported on models with Xeon E-2176M)
- Four SATA 6Gb/s mass storage interfaces
- Three DisplayPort/HDMI/DVI interfaces
- Embedded DisplayPort / LVDS (24 Bit, dual channel) interface
- Triple independent display support
- DirectX 12, OpenGL 4.5, OpenCL 2.x
- Resolution up to 4096 x 2304
- Eight PCI Express™ x1 lanes, configurable up to x4, Intel® Rapid Storage Technology support
- PEG configurable as 1×16 or 2×8 or 1×8 + 2×4
- Four USB 3.1/2.0 and four USB 2.0 interfaces
- Trusted Platform Module

COM Express Type 6



- UEFI Firmware

Technical Data

Technology	x86
Formfactor	COM Express Basic
CPU	Intel® Core™ i7-8850H (six-core, 2.6/4.3GHz, 9M cache, 45/35W cTDP), Intel® Core™ i5-8400H (quad-core, 2.5/4.2GHz, 8M cache, 45/35W cTDP), Intel® Core™ i3-8100H (quad-core, 3.0GHz, 6M cache, 45/35W cTDP), Intel® Xeon® E-2176M (six-core, 2.7/4.4GHz, 12M cache, 45/35W cTDP), Intel® Technologies: Intel® vPro, Intel® 64, Intel® Virtualization Technology (VT-x), Intel® Virtualization Technology for Directed I/O (VT-d), Intel® Trusted Execution Technology*, Intel® Adv. Encryption Standard AES-NI, Intel® Turbo Boost Technology 2.0 * not on all models
Chipset	Intel® Platform Controller Hubs (PCH) QM370 or CM246
RAM	2x 260-pin SO-DIMM socket for up to 2x 16GB DDR4 SDRAM (DDR4-2666 ¹); dual channel operation; ECC option ² ¹ Depending on SO-DIMM type ² ECC supported on models with Xeon E-2176M
Storage Interfaces	4x SATA channels (up to 6Gb/s)
USB	4x USB 3.1 (Gen 1 & 2)/2.0, 4x USB 2.0
Serial Interfaces	2x high-speed serial ports from PCH
Bus Interfaces	8x PCI Express x1 Gen 3, 1x PCI Express Graphics (PEG) x 16 Gen. 3 LPC bus (Low Pin Count bus; no DMA support)
Display Controller	Integrated Intel UHD graphics Gen. 9 3D Acceleration: DirectX® 11/12, OpenGL 4.3/4.4, OpenGL ES 2.0, OpenCL 2.x; HW accelerated Video Decode: H.264/AVC, VP8, VP9, VP9 10 Bit, H.265/HEVC 8 bit, H.265/HEVC 10 Bit, MPEG2, MJPEG, VC-1 HW accelerated Video Encode: H.264/AVC, VP8, VP9, H.265/HEVC 8 bit, H.265/HEVC 10 Bit, MPEG2, MJPEG. Triple independent display support
Display Interfaces	Display Port and HDMI/DVI: 3x Digital Display Interface, usable as DisplayPort 1.2 (up to 4096 x 2304 @ 60Hz), also usable as HDMI 1.4b or DVI (up to 4096 x 2160 @ 30Hz) 1x Embedded DisplayPort 1.4 (on variants without LVDS only); 4096 x 2304 @ 60Hz LCD: LVDS 24bit, dual-channel (not on all variants); 1920 x 1200 @ 60Hz
Network Interface	10/100/1000Base-TX (integrated in PCH, Intel® i219LM PHY)
Audio Interface	High Definition Audio
Security Device	TPM 2.0
Miscellaneous	Watchdog Timer: Initiates system reset, programmable Fan Supply: 4-pin header for 12V CPU fan, PWM speed controlled and PWM speed control for system fan supported RTC battery: External System Monitoring: Voltage, temperature, CPU fan, system fan

COM Express Type 6



Firmware	UEFI Firmware: AMI Aptio® V Security: TPM 2.0 support, TCG compliant Power Management: ACPI Active fan control USB: USB legacy support (keyboard, mouse, storage) Monitoring: System Monitoring Health Monitoring Tria Adv. Boot Device Selection: Boot device priority setting based on physical interfaces
OS Support	Windows 10 IOT Enterprise BSP for Linux (Yocto) EAPI (HW Programming Interface)
Power Requirement	Voltage: +8.5V to +20V, +5V Stby optional Power Consumption: 35 W to 55 W (typ.)
Environment	Ambient Temperature; 0° ... 60°C (operating), -25° ... 85°C (storage) Humidity: 5 ... 95% (operating, non-condensing), 5 ... 95% (storage, non-condensing)
Dimensions	125mm x 95mm x 13mm* (*Measured from module PCB bottom side to heat spreader top side. Different heights apply, when using other cooling solutions.)

Technical Data for TRIA C6B-CFLH

COM Express Type 6



Order Reference

Order No.	Description	Reference	Status*
73872	COM Express Type 6 Basic module (125mm x 95mm); CPU: Intel Xeon E-2176M, six-core, 2.7/4.4GHz, 45W TDP; Chipset: CM246; Graphics: integrated Intel HD Gen 9 (GT2); Embedded DisplayPort (eDP); 3x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; HD audio; 4x SATA; 4x USB3.1/2, 4x USB2; 8x PCIe x1 Gen 3; PEG x16 Gen 3; 2x socket for DDR4 or DDR4 ECC SO-DIMM; TPM 2.0.	MSC C6B-CFLH-2176M-NN1101C PCBFTX	OR
73874	COM Express Type 6 Basic module (125mm x 95mm); CPU: Intel Xeon E-2176M, six-core, 2.7/4.4GHz, 45W TDP; Chipset: CM246; Graphics: integrated Intel HD Gen 9 (GT2); LVDS (24 Bit, dual channel); 3x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; HD audio; 4x SATA; 4x USB3.1/2, 4x USB2; 8x PCIe x1 Gen 3; PEG x16 Gen 3; 2x socket for DDR4 or DDR4 ECC SO-DIMM; TPM 2.0.	MSC C6B-CFLH-2176M-NN1201C PCBFTX	OR
73848	COM Express Type 6 Basic module (125mm x 95mm); CPU: Intel Core i7-8850H, six-core, 2.6/4.3GHz, 45W TDP; Chipset: QM370; Graphics: integrated Intel HD Gen 9 (GT2); Embedded DisplayPort (eDP); 3x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; HD audio; 4x SATA; 4x USB3.1/2, 4x USB2; 8x PCIe x1 Gen 3; PEG x16 Gen 3; 2x socket for DDR4 SO-DIMM; TPM 2.0.	MSC C6B-CFLH-8850H-NN0101C PCBFTX	PV
73850	COM Express Type 6 Basic module (125mm x 95mm); CPU: Intel Core i7-8850H, six-core, 2.6/4.3GHz, 45W TDP; Chipset: QM370; Graphics: integrated Intel HD Gen 9 (GT2); LVDS (24 Bit, dual channel); 3x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; HD audio; 4x SATA; 4x USB3.1/2, 4x USB2; 8x PCIe x1 Gen 3; PEG x16 Gen 3; 2x socket for DDR4 SO-DIMM; TPM 2.0.	MSC C6B-CFLH-8850H-NN0201C PCBFTX	PV
73876	COM Express Type 6 Basic module (125mm x 95mm); CPU: Intel Core i5-8400H, quad-core, 2.5/4.2GHz, 45W TDP; Chipset: QM370; Graphics: integrated Intel HD Gen 9 (GT2); Embedded DisplayPort (eDP); 3x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; HD audio; 4x SATA; 4x USB3.1/2, 4x USB2; 8x PCIe x1 Gen 3; PEG x16 Gen 3; 2x socket for DDR4 SO-DIMM; TPM 2.0.	MSC C6B-CFLH-8400H-NN0101C PCBFTX	PV

COM Express Type 6



Order No.	Description	Reference	Status*
73878	COM Express Type 6 Basic module (125mm x 95mm); CPU: Intel Core i5-8400H, quad-core, 2.5/4.2GHz, 45W TDP; Chipset: QM370; Graphics: integrated Intel HD Gen 9 (GT2); LVDS (24 Bit, dual channel); 3x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; HD audio; 4x SATA; 4x USB3.1/2, 4x USB2; 8x PCIe x1 Gen 3; PEG x16 Gen 3; 2x socket for DDR4 SO-DIMM; TPM 2.0.	MSC C6B-CFLH-8400H- NN0201C PCBFTX	PV
76724	COM Express Type 6 Basic module (125mm x 95mm); CPU: Intel Core i3-8100H, quad-core, 3.0GHz, 45W TDP; Chipset: QM370; Graphics: integrated Intel HD Gen 9 (GT2); Embedded DisplayPort (eDP); 3x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; HD audio; 4x SATA; 4x USB3.1/2, 4x USB2; 8x PCIe x1 Gen 3; PEG x16 Gen 3; 2x socket for DDR4 SO-DIMM; TPM 2.0.	MSC C6B-CFLH-8100H- NN0101C PCBFTX	PV
76728	COM Express Type 6 Basic module (125mm x 95mm); CPU: Intel Core i3-8100H, quad-core, 3.0GHz, 45W TDP; Chipset: CM246; Graphics: integrated Intel HD Gen 9 (GT2); Embedded DisplayPort (eDP); 3x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; HD audio; 4x SATA; 4x USB3.1/2, 4x USB2; 8x PCIe x1 Gen 3; PEG x16 Gen 3; 2x socket for DDR4 or DDR4 ECC SO-DIMM; TPM 2.0.	MSC C6B-CFLH-8100H- NN1101C PCBFTX	OR
76726	COM Express Type 6 Basic module (125mm x 95mm); CPU: Intel Core i3-8100H, quad-core, 3.0GHz, 45W TDP; Chipset: QM370; Graphics: integrated Intel HD Gen 9 (GT2); LVDS (24 Bit, dual channel); 3x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; HD audio; 4x SATA; 4x USB3.1/2, 4x USB2; 8x PCIe x1 Gen 3; PEG x16 Gen 3; 2x socket for DDR4 SO-DIMM; TPM 2.0.	MSC C6B-CFLH-8100H- NN0201C PCBFTX	PV
76730	COM Express Type 6 Basic module (125mm x 95mm); CPU: Intel Core i3-8100H, quad-core, 3.0GHz, 45W TDP; Chipset: CM246; Graphics: integrated Intel HD Gen 9 (GT2); LVDS (24 Bit, dual channel); 3x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; HD audio; 4x SATA; 4x USB3.1/2, 4x USB2; 8x PCIe x1 Gen 3; PEG x16 Gen 3; 2x socket for DDR4 or DDR4 ECC SO-DIMM; TPM 2.0.	MSC C6B-CFLH-8100H- NN1201C PCBFTX	OR

Ordering Information for TRIA C6B-CFLH

*PV = Preferred variant; OR = on Request (in OEM quantities only)

COM Express Type 6



Accessories

Carrier Options

Order No.	Description	Reference
67295	COM Express Type 6 Evaluation Carrier Board with PCI Express x4/x16 slot, USB 3.0/2.0, GbE, SATA, DisplayPort, eDP/LVDS, VGA and HD audio interfaces; Mini PCI Express socket, SD card slot, ATX power connector and single 12V power jack. Dimensions: 170mm x 170mm (Mini-ITX form factor)	MSC C6-MB-EV-001 PCBFTX
41857	COM Express Type 6 Evaluation Carrier Board with various PCI Express x1, x4 and x16 slots, USB 3.0/2.0, GbE, SATA, DisplayPort, HDMI, LVDS, eDP, VGA, HD audio interfaces; mSATA and Mini PCI Express sockets, POST code display, ATX power connector. Dimensions: 305 x 244 mm (ATX form factor)	MSC C6-MB-EVA PCBFTX

Carrier Board TRIA C6B-KLH/CFLR/CFLH/TRIA C6C-TLU/WLU/KLU/EL/AL/BT

Cooling Solutions

Order No.	Description	Reference
1131080	Active Heatsink for C6B-SLH, C6B-KLH, C6B-CFLH and C6B-CFLR, consisting of a single-piece aluminum profile with fins, standoffs without thread (2.7mm inner diameter), screws and thermopads for the thermal contact to CPU and chipset. PWM fan 80x80x15mm.	MSC C6B-SLH-01 HSF-001
1131081	Passive Heatsink for C6B-SLH, C6B-KLH, C6B-CFLH and C6B-CFLR, consisting of a single-piece aluminum profile with fins, standoffs without thread (2.7mm inner diameter), screws and thermopads for the thermal contact to CPU and chipset.	MSC C6B-SLH-01 HSI-001
1131082	Heatspreader for C6B-SLH, C6B-KLH, C6B-CFLH and C6B-CFLR. Single-piece aluminum profile, standoffs without thread (2.7mm inner diameter), screws and thermopads for the thermal contact to CPU and chipset. No fan, no SO-DIMM cutout.	MSC C6B-SLH-01 HSP-001
1131083	Heatspreader for C6B-SLH, C6B-KLH, C6B-CFLH and C6B-CFLR. Single-piece aluminum profile, standoffs with M2.5 thread, screws and thermopads for the thermal contact to CPU and chipset. No fan, no SO-DIMM cutout.	MSC C6B-SLH-02 HSP-001

Cooling Devices for TRIA C6B-KLH/SLH/CFLR/CFLH

Memory Options

Order No.	Description	Reference
-----------	-------------	-----------

Memory Options for TRIA C6B-CFLR/CFLH. Please contact your Tria Technologies representative for information on supported memory options.

COM Express Type 6



Starter Kits

Order No.	Description	Reference
78252	Starterkit for COM Express Type 6 modules with Intel 8th or 9th generation Core processors (Coffee Lake H, Coffee Lake Refresh). Consists of the TRIA C6-MB-EV Mini-ITX platform board, suitable Heatsink with fan, two memory modules and a suitable power supply with cable kit. Please order separately the COM Express C6B-CFLH or C6B-CFLR module of your choice.	MSC C6-SK-CFLH-EV-KIT001 BRDFTX

Starter Kits for TRIA C6B-CFLR/CFLH

Tria Technologies GmbH
Industriestr. 16
76297 Stutensee
info@tria-technologies.com
tria-technologies.com

Copyright © 2024 Tria Technologies GmbH. All data is for information purposes only and is subject to change without notice. No guarantee for legal purposes is implied. Information in this document has been carefully checked, however, no responsibility for inaccuracies has to be assumed. All brand or product names may be trademarks and property of their respective owners.