


TRIA C6C-BW

Intel® Atom™ / Pentium® / Celeron® SOC

95 x 95



7 / 9W

0-+60

COM 
Express



Highlights

- Intel Pentium N3710 quad-core 1.6/2.56GHz, 6W
- Intel Celeron N3160 quad-core 1.6/2.24GHz, 6W
- Intel Celeron N3060 dual-core 1.6/2.48GHz, 6W
- Intel Celeron N3010 dual-core 1.04/2.24GHz, 4W
- Intel Atom x5-E8000 quad-core 1.04/2.0GHz, 5W
- Integrated Intel Gen. 8 HD graphics
- Up to 8GB DDR3L SDRAM, dual-channel
- Two SATA 6Gb/s mass storage interfaces
- MicroSD card socket
- DisplayPort/HDMI/DVI interface
- LVDS/embedded DisplayPort interface
- Three independent displays supported
- DirectX 11.1, OpenGL 4.2, OpenCL 1.2
- Four USB 3.0 and four USB 2.0 interfaces
- Up to five PCI Express™ x1 lanes
- Trusted Platform Module

COM Express Type 6



Technical Data

Technology	x86
Formfactor	COM Express Compact
CPU	Intel Pentium N3710 quad-core 1.6/2.56GHz, 2MB Cache, 6W TDP, Intel Celeron N3160 quad-core 1.6/2.24GHz, 2MB Cache, 6W TDP, Intel Celeron N3060 dual-core 1.6/2.48GHz, 2MB Cache, 6W TDP, Intel Celeron N3010 dual-core 1.04/2.24GHz, 2MB Cache, 4W TDP, Intel Atom x5-E8000 quad-core 1.04/2.0GHz, 2MB Cache, 5W TDP
Chipset	SOC
RAM	up to 8GB DDR3L (1333), 2x 204 pin SO-DIMM
Flash	MicroSD card socket
Storage Interfaces	2x SATA 6Gb/s
USB	4x USB 3.0/2.0, 4x USB 2.0
Bus Interfaces	Up to 5x PCI Express x1 Gen 2, LPC bus (Low Pin Count bus)
Display Controller	Integrated Intel HD graphics Gen. 8
Display Interfaces	2x Digital Display Interface (DP 1.1a (2560 x 1600 @ 60Hz or 3840x2160 @ 30Hz), DVI/HDMI 1.4b (2560 x 1600 @ 60Hz or 3840x2160 @ 30Hz)), 1x LVDS 24 bit, dual channel, 1920 x 1200 @ 60Hz 1x Embedded DisplayPort 1.4 (option, alternatively to LVDS), 2560 x 1600 @ 60Hz
Network Interface	10/100/1000Base-T (Intel i210)
Audio Interface	High Definition Audio
Security Device	TPM 1.2
Miscellaneous	Watchdog Timer: Initiates system reset, programmable Fan Supply: 4-pin header for CPU fan, PWM speed controlled and PWM speed control for system fan supported RTC battery: external System Monitoring: voltage, temperature, CPU fan, system fan
Feature Highlights	Type 6 pin-out
Firmware	AMI Aptio UEFI
OS Support	Windows 7, 8, 8.1 (embedded) BSP for Linux on request EAPI (HW Programming Interface)
Power Requirement	Wide range input +5 ... +17V, 5V Stby optional, 7 W (typ.) up to 9 W (typ.)
Environment	Ambient Temperature; 0° ... 60°C (operating), -25° ... 85°C (storage) Humidity: 5 ... 95% (operating, non-condensing), 5 ... 95% (storage, non-condensing)
Dimensions	95mm x 95mm

COM Express Type 6



Certificates	UL / CE
Cooling	Passive heat sink Active heat sink with fan Heat spreader with threaded or non-threaded standoffs
Carrier	Small carrier board as part of a starter kit; Evaluation board in ATX form factor
Memory	DDR3L SODIMMS 2GB or 4GB

Technical Data for TRIA C6C-BW

COM Express Type 6



Order Reference

Order No.	Description	Reference	Status*
66840	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Celeron N3010 dual-core 1.04/2.24GHz, 2MB L2, 4W TDP; Graphics: integrated Intel HD Gen 8; various display interfaces; LVDS; Ethernet: Intel i210 Gbit; HD audio; 2x SATA, 4x USB3/2, 4x USB2, 5x PCIe x1; TPM; 2x socket for DDR3L SO-DIMM.	MSC C6C-BW-001 PCBFTX	OR
66852	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Celeron N3060 dual-core 1.6/2.48GHz, 2MB L2, 6 TDP; Graphics: integrated Intel HD Gen 8; various display interfaces; LVDS; Ethernet: Intel i210 Gbit; HD audio; 2x SATA, 4x USB3/2, 4x USB2, 5x PCIe x1; TPM; 2x socket for DDR3L SO-DIMM.	MSC C6C-BW-002 PCBFTX	PV
66854	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Celeron N3160 quad-core 1.6/2.24GHz, 2MB L2, 6 TDP; Graphics: integrated Intel HD Gen 8; various display interfaces; LVDS; Ethernet: Intel i210 Gbit; HD audio; 2x SATA, 4x USB3/2, 4x USB2, 5x PCIe x1; TPM; 2x socket for DDR3L SO-DIMM.	MSC C6C-BW-003 PCBFTX	OR
66856	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Pentium N3710 quad-core 1.6/2.56GHz, 2MB L2, 6 TDP; Graphics: integrated Intel HD Gen 8; various display interfaces; LVDS; Ethernet: Intel i210 Gbit; HD audio; 2x SATA, 4x USB3/2, 4x USB2, 5x PCIe x1; TPM; 2x socket for DDR3L SO-DIMM.	MSC C6C-BW-004 PCBFTX	PV
68625	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Atom x5-E8000 quad-core 1.04/2.0GHz, 2MB L2, 5W TDP; Graphics: integrated Intel HD Gen 8; various display interfaces; LVDS; Ethernet: Intel i210 Gbit; HD audio; 2x SATA, 4x USB3/2, 4x USB2, 5x PCIe x1; TPM; 2x socket for DDR3L SO-DIMM.	MSC C6C-BW-005 PCBFTX	PV

COM Express Type 6



Order No.	Description	Reference	Status*
69399	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Celeron N3010 dual-core 1.04/2.24GHz, 2MB L2, 4W TDP; Graphics: integrated Intel HD Gen 8; various display interfaces; eDP; Ethernet: Intel i210 Gbit; HD audio; 2x SATA, 4x USB3/2, 4x USB2, 5x PCIe x1; TPM; 2x socket for DDR3L SO-DIMM.	MSC C6C-BW-021 PCBFTX	PV
69401	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Celeron N3060 dual-core 1.6/2.48GHz, 2MB L2, 6 TDP; Graphics: integrated Intel HD Gen 8; various display interfaces; eDP; Ethernet: Intel i210 Gbit; HD audio; 2x SATA, 4x USB3/2, 4x USB2, 5x PCIe x1; TPM; 2x socket for DDR3L SO-DIMM.	MSC C6C-BW-022 PCBFTX	OR
69403	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Celeron N3160 quad-core 1.6/2.24GHz, 2MB L2, 6 TDP; Graphics: integrated Intel HD Gen 8; various display interfaces; eDP; Ethernet: Intel i210 Gbit; HD audio; 2x SATA, 4x USB3/2, 4x USB2, 5x PCIe x1; TPM; 2x socket for DDR3L SO-DIMM.	MSC C6C-BW-023 PCBFTX	PV
69405	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Pentium N3710 quad-core 1.6/2.56GHz, 2MB L2, 6 TDP; Graphics: integrated Intel HD Gen 8; various display interfaces; eDP; Ethernet: Intel i210 Gbit; HD audio; 2x SATA, 4x USB3/2, 4x USB2, 5x PCIe x1; TPM; 2x socket for DDR3L SO-DIMM.	MSC C6C-BW-024 PCBFTX	OR
69407	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Atom x5-E8000 quad-core 1.04/2.0GHz, 2MB L2, 5W TDP; Graphics: integrated Intel HD Gen 8; various display interfaces; eDP; Ethernet: Intel i210 Gbit; HD audio; 2x SATA, 4x USB3/2, 4x USB2, 5x PCIe x1; TPM; 2x socket for DDR3L SO-DIMM.	MSC C6C-BW-025 PCBFTX	PV

Ordering Information for TRIA C6C-BW

*PV = Preferred variant; OR = on Request (in OEM quantities only)

COM Express Type 6



Accessories

Carrier Options

Order No.	Description	Reference
67295	COM Express Type 6 Evaluation Carrier Board with PCI Express x4/x16 slot, USB 3.0/2.0, GbE, SATA, DisplayPort, eDP/LVDS, VGA and HD audio interfaces; Mini PCI Express socket, SD card slot, ATX power connector and single 12V power jack. Dimensions: 170mm x 170mm (Mini-ITX form factor)	MSC C6-MB-EV-001 PCBFTX
41857	COM Express Type 6 Evaluation Carrier Board with various PCI Express x1, x4 and x16 slots, USB 3.0/2.0, GbE, SATA, DisplayPort, HDMI, LVDS, eDP, VGA, HD audio interfaces; mSATA and Mini PCI Express sockets, POST code display, ATX power connector. Dimensions: 305 x 244 mm (ATX form factor)	MSC C6-MB-EVA PCBFTX

Carrier Board TRIA C6B-SLH/TRIA C6C-SLU/BW

Cooling Solutions

Order No.	Description	Reference
1120173	Active Heatsink for C6C-BW, C6C-BT and CXC-BT, consisting of a single-piece aluminum profile with fins, standoffs without thread (2.7mm inner diameter), screws and thermopads for the thermal contact to SOC. PWM fan 80x80x15mm.	MSC C6C-BT-01 HSF-001
1119053	Passive Heatsink for C6C-BW, C6C-BT and CXC-BT, consisting of a single-piece aluminum profile with fins, standoffs without thread (2.7mm inner diameter), screws and thermopad for the thermal contact to SOC.	MSC C6C-BT-01 HSI-001
1122654	Heatspreader for C6C-BW, C6C-BT and CXC-BT. Single-piece aluminum profile, standoffs without thread (2.7mm inner diameter), screws and thermopad for the thermal contact to SOC.!	MSC C6C-BT-01 HSP-001
1122653	Heatspreader for C6C-BW, C6C-BT and CXC-BT. Single-piece aluminum profile, threaded standoffs (M2.5), screws and thermopad for the thermal contact to SOC.	MSC C6C-BT-02 HSP-001

Cooling Devices for TRIA C6C-BW/BT

Memory Options

Order No.	Description	Reference
73461	2GB SoDimm, DDR3L-1866, 256Mx8 based	MOD SODIMM DDR3 2GB PC3-14900 CL13 1B
72004	4GB SoDimm, DDR3L-1866, 512Mx8 based	MOD SODIMM DDR3 4GB PC3-14900 CL13 1B
79963	8GB SoDimm, DDR3L-1866, 512Mx8 based	MOD SODIMM DDR3 8GB PC3-14900 CL13 2B

Memory Options for TRIA C6C-BW

COM Express Type 6



Starter Kits

Order No.	Description	Reference
67555	COM Express Type 6 Starterkit for all C6C-BT and C6C-BW modules; uses the C6-MB-EV platform for Type 6 modules in Mini-ITX format; includes 2x DDR3 memory modules, suitable Heatspreader for C6C-BT and -BW modules and 12V Power Supply with Power Cable; includes Resource Drive with drivers, tools and documentation. Please order separately the COM Express C6C-BT or C6C-BW module of your choice.	MSC C6-SK-BT-EV-KIT001

Starter Kits for TRIA C6C-BW/BT

Tria Technologies GmbH
Industriestr. 16
76297 Stutensee
info@tria-technologies.com
tria-technologies.com

Copyright © 2024 Tria Technologies GmbH. All data is for information purposes only and is subject to change without notice. No guarantee for legal purposes is implied. Information in this document has been carefully checked, however, no responsibility for inaccuracies has to be assumed. All brand or product names may be trademarks and property of their respective owners.