


TRIA C6C-EL

Intel® Atom™ Series / Pentium® / Celeron® SOC



95 x 95

7 / 14W

-40-+85

COM 
Express



Highlights

- Scalable CPU performance
- Quad and dual core variants
- Power efficient processors, TDP 6 to 12W
- Extended temperature variants
- Integrated Intel Gen11LP graphics, max. 32 executing units
- Up to 32GB DDR4-3200 SDRAM, dual-channel, In-band ECC option
- Two SATA 6Gb/s mass storage interfaces
- eMMC mass storage option
- DisplayPort/HDMI interface
- LVDS/Embedded DisplayPort interface
- Three independent displays supported
- DirectX 12, OpenGL 4.5/ES 3.x, OpenCL 1.2 driver support
- Two USB 3.1 and eight USB 2.0 interfaces
- Two UARTs
- Up to eight PCI Express™ lanes
- One Gb Ethernet port
- TSN, TCC support
- UEFI Firmware
- Trusted Platform Module TPM 2.0

Technical Data

Technology	x86
Formfactor	COM Express Compact
CPU	Intel Atom® x6425RE Processor, quad-core / 4T, 1.9GHz, 32EU, IBECC, TCC 12W, IUC Intel Atom® x6416RE Processor, quad-core / 4T, 1.7GHz, 16EU, IBECC, TCC, 9W IUC Intel Atom® x6414RE Processor, quad-core / 4T, 1.5GHz, 16EU, IBECC, TCC, 9W IUC Intel Atom® x6214RE Processor, dual-core / 2T, 1.4GHz, 16EU, IBECC, TCC, 6W IUC Intel Atom® x6212RE Processor, dual-core / 2T, 1.2GHz, 16EU, IBECC, TCC, 6W IUC Intel Atom® x6425E Processor, quad-core / 4T, 2.0/3.0GHz, 32EU, IBECC, 12W EUC Intel Atom® x6413E Processor, quad-core / 4T, 1.5/3.0GHz, 16EU, IBECC, 9W EUC Intel Atom® x6211E Processor, dual-core / 2T, 1.3/3.0GHz, 16EU, IBECC, 6W EUC Intel® Pentium® J6426 Processor, quad-core / 4T, 2.0/3.0GHz, 32EUs, 10W, PUC Intel® Pentium® N6415 Processor, quad-core / 4T, 1.2/3.0GHz, 16EU, 6W, PUC Intel® Celeron® J6413 Processor, quad-core / 4T, 1.8/3.0GHz, 16EU, 10W, PUC Intel® Celeron® N6211 Processor, dual-core / 2T, 1.2/3.0GHz, 16EU, 6W, PUC Intel® Technologies: Enhanced Intel® SpeedStep® Technology Intel® Virtualization Technology (VTx-2, VT-d) Intel® Trusted Execution Engine (TXE) Intel® Time Coordinated Computing (TCC) Precision Time Measurement (PTM) Precision Time Measurement (PTP) IUC - Intel Industrial Use Conditions EUC - Intel Embedded Use Conditions PUC - Intel PC Client Use Conditions
Chipset	SOC
RAM	2x 260-pin SO-DIMM socket for up to 2x 16 GB (dual channel operation) or 1x 16 GB (single channel operation) DDR4-3200 (max. transfer speed depending on memory type) In-band ECC (on selected variants)
Flash	On-board eMMC mass storage option, scalable capacity up to 256GB
Storage Interfaces	Up to 2x SATA 6Gb/s
USB	2x USB 3.1 8x USB 2.0
Serial Interfaces	Two UARTS
Bus Interfaces	8x PCI Express Gen 3, up to 6 root ports LPC bus (Low Pin Count bus; no DMA support)
Display Controller	Integrated Intel graphics Gen11LP Up to 32 execution units (EU) DirectX 12, OpenGL 4.5/ES 3.x, OpenCL 1.2 driver support Media codec support: MPEG2, H.264 (L5.2), VC-1, WMV9, VP8, VP9, JPEG/MPEG, H.265 (HEVC)
Display Interfaces	Three independent displays supported: 2x Digital Display Interface (DP 1.2/1.3/1.4 (max. 4096 x 2160 @ 60Hz), HDMI 1.4b/2.0b (max. 4K @ 60Hz) 1x Embedded DisplayPort 1.3 (on variants without LVDS only); max. 4096 x 2160 @ 60Hz, LVDS 24bit, dual-channel (not on all variants); max. 1920 x 1200 @ 60Hz
Network Interface	10/100/1000Base-T (SoC integrated controller) Supports Time-Sensitive Networking (TSN) and Time Coordinated Computing (TCC)
Audio Interface	High Definition Audio
Security Device	TPM 2.0

COM Express Type 6



Miscellaneous	Watchdog Timer: Initiates system reset, programmable Fan Supply: 4-pin header for CPU fan, PWM speed controlled and PWM speed control for system fan supported RTC battery: external System Monitoring: voltage, temperature, CPU fan, system fan
Feature Highlights	Type 6 pin-out
Firmware	AMI Aptio UEFI
OS Support	Windows 10 IoT Enterprise RS5 (64bit) Linux (Yocto Project) Kernel 5.4
Power Requirement	Wide range input +8.5 ... +20V, 5V Stby optional, 7 W to 14 W (typ.)
Environment	Ambient Temperature; 0° ... 60°C (operating), -25° ... 85°C (storage) Extended temp. variants: -40 ... +85°C (operating) Humidity: 5 ... 95% (operating, non-condensing), 5 ... 95% (storage, non-condensing)
Dimensions	95mm x 95mm
Cooling	Passive heat sink Active heat sink with fan Heat spreader with threaded or non-threaded standoffs
Carrier	Evaluation/carrier board options

Technical Data for TRIA C6C-EL

COM Express Type 6

Order Reference

Order No.	Description	Reference	Status*
86110	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Atom x6425RE, quad-core, 1.9GHz, 12W; Graphics: Intel Gen 11LP; 32 EUs; 2x DP/HDMI; LVDS; Ethernet: Intel integrated Gbit; HD audio; 2x SATA, 2x USB3/2, 6x USB2, 8x PCIe Gen 3; TPM 2.0; 2x socket for DDR4 SO-DIMM, in-band ECC; -40...+85°C (recommended for 24/7 operation)	MSC C6C-EL-X6425RE- NN221I PCBFTX	PV
86122	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Atom x6414RE, quad-core, 1.5GHz, 9W; Graphics: Intel Gen 11LP; 16 EUs; 2x DP/HDMI; LVDS; Ethernet: Intel integrated Gbit; HD audio; 2x SATA, 2x USB3/2, 6x USB2, 8x PCIe Gen 3; TPM 2.0; 2x socket for DDR4 SO-DIMM, in-band ECC; -40...+85°C (recommended for 24/7 operation)	MSC C6C-EL-X6414RE- NN221I PCBFTX	PV
86124	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Atom x6212RE, dual-core, 1.2GHz, 6W; Graphics: Intel Gen 11LP; 16 EUs; 2x DP/HDMI; LVDS; Ethernet: Intel integrated Gbit; HD audio; 2x SATA, 2x USB3/2, 6x USB2, 8x PCIe Gen 3; TPM 2.0; 2x socket for DDR4 SO-DIMM, in-band ECC; -40...+85°C (recommended for 24/7 operation)	MSC C6C-EL-X6212RE- NN221I PCBFTX	PV
86126	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Atom x6425E, quad-core, 2.0GHz, 12W; Graphics: Intel Gen 11LP; 32 EUs; 2x DP/HDMI; LVDS; Ethernet: Intel integrated Gbit; HD audio; eMMC 32GB 2x SATA, 2x USB3/2, 6x USB2, 8x PCIe Gen 3; TPM 2.0; 2x socket for DDR4 SO-DIMM, in-band ECC; -40...+85°C	MSC C6C-EL-X6425E- N5201I PCBFTX	OR
86128	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Atom x6413E, quad-core, 1.5GHz, 9W; Graphics: Intel Gen 11LP; 16 EUs; 2x DP/HDMI; LVDS; Ethernet: Intel integrated Gbit; HD audio; 2x SATA, 2x USB3/2, 6x USB2, 8x PCIe Gen 3; TPM 2.0; 2x socket for DDR4 SO-DIMM, in-band ECC; -40...+85°C	MSC C6C-EL-X6413E- NN221I PCBFTX	OR
86130	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Atom x6211E, dual-core, 1.3GHz, 6W; Graphics: Intel Gen 11LP; 16 EUs; 2x DP/HDMI; LVDS; Ethernet: Intel integrated Gbit; HD audio; 2x SATA, 2x USB3/2, 6x USB2, 8x PCIe Gen 3; TPM 2.0; 2x socket for DDR4 SO-DIMM, in-band ECC; -40...+85°C	MSC C6C-EL-X6211E- NN221I PCBFTX	OR

COM Express Type 6



Order No.	Description	Reference	Status*
86132	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Pentium J6426, quad-core, 2.0GHz, 10W; Graphics: Intel Gen 11LP; 32 EUs; 2x DP/HDMI; eDP; Ethernet: Intel integrated Gbit; HD audio; 2x SATA, 2x USB3/2, 6x USB2, 8x PCIe Gen 3; TPM 2.0; 2x socket for DDR4 SO-DIMM;	MSC C6C-EL-J6426- NN121C PCBFTX	OR
86134	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Celeron J6413, quad-core, 1.8GHz, 10W; Graphics: Intel Gen 11LP; 16 EUs; 2x DP/HDMI; eDP; Ethernet: Intel integrated Gbit; HD audio; 2x SATA, 2x USB3/2, 6x USB2, 8x PCIe Gen 3; TPM 2.0; 2x socket for DDR4 SO-DIMM;	MSC C6C-EL-J6413- NN121C PCBFTX	OR
95063	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Pentium J6426, quad-core, 2.0GHz, 10W; Graphics: Intel Gen 11LP; 32 EUs; 2x DP/HDMI; LVDS; Ethernet: Intel integrated Gbit; HD audio; 2x SATA, 2x USB3/2, 6x USB2, 8x PCIe Gen 3; TPM 2.0; 2x socket for DDR4 SO-DIMM;	MSC C6C-EL-J6426- NN221C PCBFTX	OR
95041	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Celeron J6413, quad-core, 1.8GHz, 10W; Graphics: Intel Gen 11LP; 16 EUs; 2x DP/HDMI; LVDS; Ethernet: Intel integrated Gbit; HD audio; 2x SATA, 2x USB3/2, 6x USB2, 8x PCIe Gen 3; TPM 2.0; 2x socket for DDR4 SO-DIMM;	MSC C6C-EL-J6413- NN221C PCBFTX	OR

Ordering Information for TRIA C6C-EL

*PV = Preferred variant; OR = on Request (in OEM quantities only)

Accessories

Carrier Options

Order No.	Description	Reference
67295	COM Express Type 6 Evaluation Carrier Board with PCI Express x4/x16 slot, USB 3.0/2.0, GbE, SATA, DisplayPort, eDP/LVDS, VGA and HD audio interfaces; Mini PCI Express socket, SD card slot, ATX power connector and single 12V power jack. Dimensions: 170mm x 170mm (Mini-ITX form factor)	MSC C6-MB-EV-001 PCBFTX
41857	COM Express Type 6 Evaluation Carrier Board with various PCI Express x1, x4 and x16 slots, USB 3.0/2.0, GbE, SATA, DisplayPort, HDMI, LVDS, eDP, VGA, HD audio interfaces; mSATA and Mini PCI Express sockets, POST code display, ATX power connector. Dimensions: 305 x 244 mm (ATX form factor)	MSC C6-MB-EVA PCBFTX

Carrier Board TRIA C6B-KLH/CFLR/CFLH/TRIA C6C-TLU/WLU/KLU/EL/AL/BT

Cooling Solutions

Order No.	Description	Reference
82415	Passive Heatsink for C6C-EL (Atom versions only), consisting of a single-piece aluminum profile with fins, standoffs without thread (2.7mm inner diameter), screws and thermopad for the thermal contact to SOC.	MSC C6C-EL-01 HSI-001
85123	Heatspreader for C6C-EL (Atom versions only). Single-piece aluminum profile with standoffs without thread (2.7mm inner diameter), screws and thermopad for the thermal contact to SOC.	MSC C6C-EL-01 HSP-001
85930	Passive Heatsink for C6C-EL (Pentium/Celeron versions only), consisting of a single-piece aluminum profile with fins, standoffs without thread (2.7mm inner diameter), screws and thermopad for the thermal contact to SOC.	MSC C6C-EL-02 HSI-001
85124	Heatspreader for C6C-EL (Atom versions only). Single-piece aluminum profile with threaded standoffs (M2.5), screws and thermopad for the thermal contact to SOC.	MSC C6C-EL-02 HSP-001
85941	Heatspreader for C6C-EL (Pentium/Celeron versions only). Single-piece aluminum profile with standoffs without thread (2.7mm inner diameter), screws and thermopad for the thermal contact to SOC.	MSC C6C-EL-03 HSP-001
85942	Heatspreader for C6C-EL (Pentium/Celeron versions only). Single-piece aluminum profile with threaded standoffs (M2.5), screws and thermopad for the thermal contact to SOC.	MSC C6C-EL-04 HSP-001

Cooling Devices for TRIA C6C-EL

Order No.	Description	Reference
79809	Fan kit for Heatsink MSC HCA-ALP/RLP/MLH-0x HSI-xxx, MSC C6B-ALP/RLP/MLH-0x HSI-xxx, MSC C6B-TLH-0x HSI-xxx, MSC C6C-ALP/RLP-0x HSI-xxx, MSC C6C-TLU-0x HSI-xxx, MSC C6C-WLU-0x HSI-xxx, MSC C6C-ALN/ASL-0x HSI-xxx, MSC C6C-EL-0x HSI-xxx, MSC C6C-RYZx-0x HSI-xxx, PWM fan 80x80x15mm.	MSC C6C-FANKIT-01- HSF-001

Fan Kit for COM Express Heatsinks

Memory Options

Description	Description	Reference
117594	8GB DDR4-3200 SO-DIMM, Commercial Temp.	MOD SODIMM DDR4 8GB PC4-25600 CL22
97869	16GB DDR4-3200 SO-DIMM, Commercial Temp.	MOD SODIMM DDR4 16GB PC4-25600 CL22 2B
93718	8GB DDR4-3200 SO-DIMM, Wide Temp.	MOD SODIMM DDR4 8GB PC4-25600 CL22 1B
93720	8GB DDR4-3200 SO-DIMM, Industrial Temp.	MOD SODIMM DDR4 8GB PC4-25600 CL22 1B

Memory Options for TRIA C6C-EL

Please contact your Tria Technologies representative for information on supported memory options.

Tria Technologies GmbH
Industriestr. 16
76297 Stutensee
info@tria-technologies.com
tria-technologies.com

Copyright © 2024 Tria Technologies GmbH. All data is for information purposes only and is subject to change without notice. No guarantee for legal purposes is implied. Information in this document has been carefully checked, however, no responsibility for inaccuracies has to be assumed. All brand or product names may be trademarks and property of their respective owners.