


TRIA C6C-SLU

Intel® Core™ 6th Generation



95 x 95

17 / 19W

0-+60

COM 
Express



Highlights

- Intel Core i7-6600U dual-core 2.6/3.4GHz, 4MB L2, 15W TDP, 7.5/25W cTDP
- Intel Core i5-6300U dual-core 2.4/3.0GHz, 3MB L2, 15W TDP, 7.5/25W cTDP
- Intel Core i3-6100U dual-core 2.3GHz, 3MB L2, 15W TDP, 7.5 cTDP
- Intel Celeron 3955U dual-core 2.0GHz, 2MB L2, 15W TDP, 10W cTDP
- Integrated Intel Gen. 9 HD graphics
- Up to 32 GB DDR4-2133 SDRAM, dual-channel
- Three SATA 6Gb/s mass storage interfaces
- MicroSD card socket
- DisplayPort/HDMI/DVI interface
- LVDS/embedded DisplayPort interface
- Three independent displays supported
- DirectX 12, OpenGL 4.4, OpenCL 2.x
- Four USB 3.0/2.0 and four USB 2.0 interfaces
- Eight PCI Express™ x1 lanes
- Trusted Platform Module

COM Express Type 6



Technical Data

Technology	x86
Formfactor	COM Express Compact
CPU	Intel Core i7-6600U dual-core 2.6/3.4GHz, 4MB L2, 15W TDP, 7.5/25W cTDP, Intel Core i5-6300U dual-core 2.4/3.0GHz, 3MB L2, 15W TDP, 7.5/25W cTDP, Intel Core i3-6100U dual-core 2.3GHz, 3MB L2, 15W TDP, 7.5 cTDP, Intel Celeron 3955U dual-core 2.0GHz, 2MB L2, 15W TDP, 10W cTDP
Chipset	Integrated in Multi-Chip-Package
RAM	2x 260-pin SO-DIMM socket for up to 2x 16 GB DDR4 SDRAM (DDR4-2133); dual channel operation
Flash	MicroSD card socket
Storage Interfaces	Up to 3x SATA 6Gb/s
USB	4x USB 3.0/2.0, 4x USB 2.0
Serial Interfaces	2x high-speed serial ports from PCH
Bus Interfaces	Up to 8x PCI Express x1 Gen 2 or Gen3 (depending on processor variant), LPC bus (Low Pin Count bus; no DMA support)
Display Controller	Integrated Intel HD graphics Gen. 9
Display Interfaces	2x Digital Display Interface (DP 1.2 (4096 x 2304 @ 60Hz), DVI/HDMI 1.4b (2560 x 1600 @ 60Hz or 4096 x 2160 @ 24Hz)) 1x Embedded DisplayPort 1.4 (on variants without LVDS only); 4096 x 2304 @ 60Hz, LVDS 24bit, dual-channel (not on all variants); 1920 x 1200 @ 60Hz
Network Interface	10/100/1000Base-TX (Intel i219)
Audio Interface	High Definition Audio
Security Device	TPM 1.2, TPM 2.0 (optional)
Miscellaneous	Watchdog Timer: Initiates system reset, programmable Fan Supply: 4-pin header for CPU fan, PWM speed controlled and PWM speed control for system fan supported RTC battery: external System Monitoring: voltage, temperature, CPU fan, system fan
Feature Highlights	Type 6 pin-out
Firmware	AMI Aptio UEFI
OS Support	Windows 7, 8, 8.1, 10 (embedded) BSP for Linux on request EAPI (HW Programming Interface)
Power Requirement	12V +-5%, 5V Stby optional, 17 W to 19 W (typ.)
Environment	Ambient Temperature; 0° ... 60°C (operating), -25° ... 85°C (storage) Humidity: 5 ... 95% (operating, non-condensing), 5 ... 95% (storage, non-condensing)
Dimensions	95mm x 95mm

COM Express Type 6



Certificates	UL / CE
--------------	---------

Technical Data for TRIA C6C-SLU

Order Reference

Order No.	Description	Reference	Status *
67586	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Celeron 3955U, dual-core, 2.0GHz, 15W TDP, 10W cTDP; Graphics: integrated Intel HD Gen 9 (GT1); LVDS; 2x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; TPM 1.2 HD audio; 2x SATA, 4x USB3, 4x USB2, 8x PCIe x1 Gen 2; 2x socket for DDR4 SO-DIMM.	MSC C6C-SLU-001 PCBFTX	OR
67588	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel i3-6100U, dual-core, 2.3GHz, 15W TDP, 7.5W cTDP; Graphics: integrated Intel HD Gen 9 (GT2); LVDS; 2x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; TPM 1.2 HD audio; 2x SATA, 4x USB3, 4x USB2, 8x PCIe x1 Gen 2; 2x socket for DDR4 SO-DIMM.	MSC C6C-SLU-002 PCBFTX	OR
67590	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel i5-6300U, dual-core, 2.4/3.0GHz, 15W TDP, 7.5/25W cTDP; Graphics: integrated Intel HD Gen 9 (GT2); LVDS; 2x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; TPM 1.2 HD audio; 3x SATA, 4x USB3, 4x USB2, 8x PCIe x1 Gen 3; 2x socket for DDR4 SO-DIMM.	MSC C6C-SLU-003 PCBFTX	OR
67592	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel i7-6600U, dual-core, 2.6/3.4GHz, 15W TDP, 7.5/25W cTDP; Graphics: integrated Intel HD Gen 9 (GT2); LVDS; 2x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; TPM 1.2 HD audio; 3x SATA, 4x USB3, 4x USB2, 8x PCIe x1 Gen 3; 2x socket for DDR4 SO-DIMM.	MSC C6C-SLU-005 PCBFTX	OR
67713	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Celeron 3955U, dual-core, 2.0GHz, 15W TDP, 10W cTDP; Graphics: integrated Intel HD Gen 9 (GT1); eDP; 2x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; TPM 1.2 HD audio; 2x SATA, 4x USB3, 4x USB2, 8x PCIe x1 Gen 2; 2x socket for DDR4 SO-DIMM.	MSC C6C-SLU-011 PCBFTX	OR
67715	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel i3-6100U, dual-core, 2.3GHz, 15W TDP, 7.5W cTDP; Graphics: integrated Intel HD Gen 9 (GT2); eDP; 2x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; TPM 1.2 HD audio; 2x SATA, 4x USB3, 4x USB2, 8x PCIe x1 Gen 2; 2x socket for DDR4 SO-DIMM.	MSC C6C-SLU-012 PCBFTX	OR
67717	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel i5-6300U, dual-core, 2.4/3.0GHz, 15W TDP, 7.5/25W cTDP; Graphics: integrated Intel HD Gen 9 (GT2); eDP; 2x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; TPM 1.2 HD audio; 3x SATA, 4x USB3, 4x USB2, 8x PCIe x1 Gen 3; 2x socket for DDR4 SO-DIMM.	MSC C6C-SLU-013 PCBFTX	OR

COM Express Type 6



Order No.	Description	Reference	Status*
67719	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel i7-6600U, dual-core, 2.6/3.4GHz, 15W TDP, 7.5/25W cTDP; Graphics: integrated Intel HD Gen 9 (GT2); eDP; 2x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; TPM 1.2 HD audio; 3x SATA, 4x USB3, 4x USB2, 8x PCIe x1 Gen 3; 2x socket for DDR4 SO-DIMM.	MSC C6C-SLU-015 PCBFTX	OR
84391	COM Express Type 6 Compact module (95mm x 95mm); CPU: Intel Core i3-6100U, dual-core, 2.3GHz, 15W TDP; Graphics: integrated Intel HD Gen 9 (GT2); LVDS; 2x DP/HDMI/DVI; Ethernet: Intel i219 Gbit; TPM 2.0 HD audio; 2x SATA, 4x USB3, 4x USB2, 8x PCIe x1 Gen 2; 2x socket for DDR4 SO-DIMM.	MSC C6C-SLU-202 PCBFTX	OR

Ordering Information for TRIA C6C-SLU

*PV = Preferred variant; OR = on Request (in OEM quantities only)

COM Express Type 6



Accessories

Carrier Boards

Order No.	Description	Reference
67295	COM Express Type 6 Evaluation Carrier Board with PCI Express x4/x16 slot, USB 3.0/2.0, GbE, SATA, DisplayPort, eDP/LVDS, VGA and HD audio interfaces; Mini PCI Express socket, SD card slot, ATX power connector and single 12V power jack. Dimensions: 170mm x 170mm (Mini-ITX form factor)	MSC C6-MB-EV-001 PCBFTX
41857	COM Express Type 6 Evaluation Carrier Board with various PCI Express x1, x4 and x16 slots, USB 3.0/2.0, GbE, SATA, DisplayPort, HDMI, LVDS, eDP, VGA, HD audio interfaces; mSATA and Mini PCI Express sockets, POST code display, ATX power connector. Dimensions: 305 x 244 mm (ATX form factor)	MSC C6-MB-EVA PCBFTX

Carrier Board TRIA C6B-SLH/TRIA C6C-SLU/BW

Cooling Solutions

Order No.	Description	Reference
1129634	Active Heatsink for C6C-SLU and C6C-KLU, consisting of a single-piece aluminum profile with fins, milled standoffs without thread (2.7mm inner diameter), screws and thermopads for the thermal contact to SOC. PWM fan 80x80x15mm.	MSC C6C-SLU-01 HSF-001
1129633	Passive Heatsink for C6C-SLU and C6C-KLU, consisting of a single-piece aluminum profile with fins, milled standoffs without thread (2.7mm inner diameter), screws and thermopad for the thermal contact to SOC.	MSC C6C-SLU-01 HSI-001
1129631	Heatspreader for C6C-SLU and C6C-KLU. Single-piece aluminum profile, milled standoffs without thread (2.7mm inner diameter), screws and thermopad for the thermal contact to SOC.	MSC C6C-SLU-01 HSP-001
1129632	Heatspreader for C6C-SLU and C6C-KLU. Single-piece aluminum profile with milled standoffs with M2.5 thread, screws and thermopad for the thermal contact to SOC.	MSC C6C-SLU-02 HSP-001

Cooling Devices for TRIA C6C-KLU/SLU

Memory Options

Please contact your Tria Technologies representative for information on supported memory options.

COM Express Type 6



Starter Kits

Order No.	Description	Reference
68454	Starter kit for COM Express Type 6 modules TRIA C6C-SLU/KLU with Intel 6th/7th generation Core processors (Skylake U, Kaby Lake U). Consists of the TRIA C6-MB-EV Mini-ITX platform board, suitable Heatsink with fan, two memory modules and a suitable power supply with cable kit. Please order separately the COM Express C6C-SLU/KLU module of your choice.	MSC C6-SK-SLU-EV-KIT001 BRDFTX

Starter Kits for TRIA C6C-KLU/SLU

Tria Technologies GmbH
Industriestr. 16
76297 Stutensee
info@tria-technologies.com
tria-technologies.com

Copyright © 2024 Tria Technologies GmbH. All data is for information purposes only and is subject to change without notice. No guarantee for legal purposes is implied. Information in this document has been carefully checked, however, no responsibility for inaccuracies has to be assumed. All brand or product names may be trademarks and property of their respective owners.