


## TRIA HMM-RLP

Intel® Core™ 13th Generation



95 x 70

tbd

-40 - +85°C



COM+HPC®

## Highlights

- COM-HPC Mini module
- 13th Gen Intel® Core™ processors
- Scalable CPU performance, up to fourteen cores, twenty threads
- Industrial grading options (Intel® TCC, TSN, IBEC, ext. Temp., 24/7)
- LPDDR5-6400 main memory, memory-down, up to 64GB, In-band ECC option
- Intel® Iris® Xe architecture Graphics, up to 96 EUs
- Up to four independent displays, embedded DisplayPort interface
- Supports COM-HPC Mini Config 1, 2, 3 (optional)
- Up to two DisplayPort/HDMI interface (DDI)
- Up to two USB4 port, up to four USB 3.2 Gen2x1, eight USB 2.0 ports
- PCI Express® Gen 3, up to 8 lanes with flexible bifurcation options, PCI Express® Gen 4, up to 2x4
- Dual MIPI-CSI
- Optional on-board NVMe SSD, 128GB, 256GB, optional two SATA 6Gb/s mass storage interfaces
- Two 2.5 Gb Ethernet ports (Intel® i226)
- Two UARTs

## Technical Data

|                        |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |          |         |   |         |          |        |         |         |          |        |         |         |
|------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------|---------|---|---------|----------|--------|---------|---------|----------|--------|---------|---------|
| Technology             | x86                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |          |         |   |         |          |        |         |         |          |        |         |         |
| Formfactor / Interface | COM-HPC Mini                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |          |         |   |         |          |        |         |         |          |        |         |         |
| CPU                    | <p>13th Gen Intel® Core™ processors</p> <p>H-series</p> <p>Intel® Core™ i7-13800HE 6P+8E/20T, 2.5GHz, 96 EUs, 24MB L3, 45/35W cTDP</p> <p>Intel® Core™ i7-13800HRE 6P+8E/20T, 2.5GHz, 96 EUs, 24MB L3, 45/35W cTDP, TCC/TSN, IBECC, ET</p> <p>Intel® Core™ i5-13600HE 4P+8E/16T, 2.7GHz, 80 EUs, 18MB L3, 45/35W cTDP</p> <p>Intel® Core™ i5-13600HRE 4P+8E/16T, 2.7GHz, 80 EUs, 18MB L3, 45/35W cTDP, TCC/TSN, IBECC, ET</p> <p>Intel® Core™ i3-13300HE 4P+4E/12T, 2.1GHz, 48 EUs, 12MB L3, 45/35W cTDP</p> <p>Intel® Core™ i3-13300HRE 4P+4E/12T, 2.1GHz, 48 EUs, 12MB L3, 45/35W cTDP, TCC/TSN, IBECC, ET</p> <p>P-series</p> <p>Intel® Core™ i7-1370PE 6P+8E/20T, 1.9GHz, 96 EUs, 24MB L3, 28/20W cTDP</p> <p>Intel® Core™ i7-1370PRE 6P+8E/20T, 1.9GHz, 96 EUs, 24MB L3, 28/20W cTDP, TCC/TSN, IBECC, ET</p> <p>Intel® Core™ i5-1350PE 4P+8E/16T, 1.8GHz, 80 EUs, 12MB L3, 28/20W cTDP</p> <p>Intel® Core™ i5-1350PRE 4P+8E/16T, 1.8GHz, 80 EUs, 12MB L3, 28/20W cTDP, TCC/TSN, IBECC, ET</p> <p>Intel® Core™ i5-1340PE 4P+8E/16T, 1.8GHz, 80 EUs, 12MB L3, 28/20W cTDP</p> <p>Intel® Core™ i3-1320PE 4P+4E/12T, 1.7GHz, 48 EUs, 12MB L3, 28/20W cTDP</p> <p>Intel® Core™ i3-1320PRE 4P+4E/12T, 1.7GHz, 48 EUs, 12MB L3, 28/20W cTDP, TCC/TSN, IBECC, ET</p> <p>U-series</p> <p>Intel® Core™ i7-1365UE 2P+8E/12T, 1.7GHz, 96 EUs, 12MB L3, 15/12W cTDP</p> <p>Intel® Core™ i7-1365URE 2P+8E/12T, 1.7GHz, 96 EUs, 12MB L3, 15/12W cTDP, TCC/TSN, IBECC, ET</p> <p>Intel® Core™ i5-1345UE 2P+8E/12T, 1.4GHz, 80 EUs, 12MB L3, 15/12W cTDP</p> <p>Intel® Core™ i5-1345URE 2P+8E/12T, 1.4GHz, 80 EUs, 12MB L3, 15/12W cTDP, TCC/TSN, IBECC, ET</p> <p>Intel® Core™ i5-1335UE 2P+8E/12T, 1.3GHz, 80 EUs, 12MB L3, 15/12W cTDP</p> <p>Intel® Core™ i3-1315UE 2P+4E/8T, 1.2GHz, 64 EUs, 10MB L3, 15/12W cTDP</p> <p>Intel® Core™ i3-1315URE 2P+4E/8T, 1.2GHz, 64 EUs, 10MB L3, 15/12W cTDP, TCC/TSN, IBECC, ET</p> <p>Intel® Processor U300E 1P+4E/6T, 1.1GHz, 48 EUs, 8MB L3, 15/12W cTDP</p> <p>Note: P core base frequency at nominal TDP shown, other clock frequencies supported</p> |          |         |   |         |          |        |         |         |          |        |         |         |
| Chipset                | Integrated into SoC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |          |         |   |         |          |        |         |         |          |        |         |         |
| RAM                    | LPDDR5 memory, up to 6400 MT/s (variant dependent); memory-down<br>Capacity options: 4GB, 8GB, 16GB, 32GB, 64GB                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |          |         |   |         |          |        |         |         |          |        |         |         |
| Storage Interfaces     | 2x SATA channels (up to 6Gb/s), optional, mutually exclusive with COM-HPC PCIe[6,7]<br>Optional on-board NVMe, 128GB, 256GB, mutually exclusive with COM-HPC PCIe[12:15]                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |          |         |   |         |          |        |         |         |          |        |         |         |
| USB                    | Up to two USB4 on COM-HPC SS Lane 2, 3 (mutually exclusive with DD1) and Lane 4, 5 (mutually exclusive with USB3 #2, #3)<br>Two USB 3.2 Gen 2x1 on COM-HPC SS Lane 6, 7 (USB3 #0, #1)<br>Up to two USB 3.2 Gen 2x1 on COM-HPC SS Lane 4, 5 (mutually exclusive with USB4 #1)<br>8x USB 2.0 on COM-HPC USB[0:7]<br>Note: supported interfaces depending on COM-HPC carrier design. Config 3 on request                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |          |         |   |         |          |        |         |         |          |        |         |         |
| Serial Interfaces      | 2x high-speed serial ports                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |          |         |   |         |          |        |         |         |          |        |         |         |
| Bus Interfaces         | PCI Express® Gen 4, up to 2x4 on COM-HPC PCIe[8:15], PCIe[12:15] mutually exclusive with on-board NVMe<br>PCI Express® Gen 3, up to 8 lanes, flexible bifurcation options on COM-HPC PCIe[0:7], PCIe[6,7] mutually exclusive with COM-HPC SATA[0,1]<br>Note: For different bifurcation options, dedicated BIOS images required                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |          |         |   |         |          |        |         |         |          |        |         |         |
| Display Controller     | Intel® Iris® Xe architecture Graphics, up to 96 execution units (EU)<br>H.264/AVC, H.265/HEVC, AV1, MJPEG encode/decode/transcode                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |          |         |   |         |          |        |         |         |          |        |         |         |
| Display Interfaces     | Up to four independent display streams<br>Supports COM-HPC Mini Config 1, 2. Config 3 on request<br>Up to two DisplayPort/HDMI interface (DDI), DP 1.4a, HDMI 2.1<br>Up to two USB4/USB-C ports (DP tunneling, DP Alt Mode)<br>1x Embedded DisplayPort 1.4b<br><table><tr><td>Config 1</td><td>2x DDI</td><td>-</td><td>4x USB3</td></tr><tr><td>Config 2</td><td>1x DDI</td><td>1x USB4</td><td>4x USB3</td></tr><tr><td>Config 3</td><td>1x DDI</td><td>2x USB4</td><td>2x USB3</td></tr></table> <p>Note: supported interfaces depending on COM-HPC carrier design.</p>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Config 1 | 2x DDI  | - | 4x USB3 | Config 2 | 1x DDI | 1x USB4 | 4x USB3 | Config 3 | 1x DDI | 2x USB4 | 2x USB3 |
| Config 1               | 2x DDI                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | -        | 4x USB3 |   |         |          |        |         |         |          |        |         |         |
| Config 2               | 1x DDI                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 1x USB4  | 4x USB3 |   |         |          |        |         |         |          |        |         |         |
| Config 3               | 1x DDI                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 2x USB4  | 2x USB3 |   |         |          |        |         |         |          |        |         |         |

|                          |                                                                                                                                                                                                                                                                                                                                                     |
|--------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Network Interface</b> | Two 10/100/1000Base-TX, 2.5Gb <sup>1</sup> based on Intel i226, TSN support<br><sup>1</sup> Available bandwidths depending on carrier design<br>I-Temp variants: Intel® i226-IT<br>C-Temp variants: Intel® i226-LM                                                                                                                                  |
| <b>Audio Interface</b>   | High Definition Audio (HDA)<br>Optional SoundWire (COM-HPC SNDW[2:3] mutually exclusive with HDA)                                                                                                                                                                                                                                                   |
| <b>Security Device</b>   | TPM 2.0                                                                                                                                                                                                                                                                                                                                             |
| <b>Miscellaneous</b>     | 2x MIPI CSI camera interface on FFC connectors<br>Watchdog Timer:<br>Initiates system reset, programmable<br>Fan Supply:<br>4-pin header for CPU fan, PWM speed controlled<br>and PWM speed control for system fan supported<br>RTC battery:<br>external<br>System Monitoring:<br>voltage, temperature, CPU fan, system fan<br>User space in EEPROM |
| <b>Firmware</b>          | UEFI Firmware:<br>AMI Aptio® V<br>Security:<br>TPM 2.0 support, TCG compliant<br>Power Management:<br>ACPI<br>Active fan control<br>USB:<br>USB legacy support (keyboard, mouse, storage)<br>Monitoring:<br>System Monitoring<br>Health Monitoring<br>Tria Adv. Boot Device Selection:<br>Boot device priority setting based on physical interfaces |
| <b>OS Support</b>        | Windows 11 IoT Enterprise LTSC<br>BSP for Linux (Yocto)                                                                                                                                                                                                                                                                                             |
| <b>Power Requirement</b> | Voltage:<br>+8V to +20V, +3V RTC voltage<br>Power Consumption:<br>tbd W to tbd W (typ.)                                                                                                                                                                                                                                                             |
| <b>Environment</b>       | Ambient Temperature:<br>0° ... 60°C (operating)<br>-25° ... 85°C (storage)<br>Extended temp. variants: -40 ... +85°C (operating)<br>Humidity:<br>5 ... 95% (operating, non-condensing),<br>5 ... 95% (storage, non-condensing)                                                                                                                      |
| <b>Dimensions</b>        | 95mm x 70mm                                                                                                                                                                                                                                                                                                                                         |

Technical Data for TRIA HMM-RLP

## Order Reference

| Order No. | Description                                                                                                                                                                                                                                                                                                                                                            | Reference                                        |    |
|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----|
| 120723    | COM-HPC Mini module (95mm x 70mm);<br>CPU: Intel i7-13800HRE 14C/20T, vPro, 1.8GHz, 35W cTDP;<br>Graphics: Intel® Iris® Xe 96 EUs; 2x DP/HDMI; 1x eDP;<br>Ethernet: 2x Intel i226-IT Gbit, TSN; HD audio; TPM 2.0;<br>2x SATA, 1x USB4, 4x USB3, 8x USB2, PCIe Gen 4 2x4, PCIe Gen 3 8x;<br>16GB LPDDR5-6400 memory;<br>-40...+85°C, recommended for 24/7 operation.   | MSC<br>HMM-<br>RLP-13800HRE-4N03<br>1I<br>PCBFTX | PV |
| 120725    | COM-HPC Mini module (95mm x 70mm);<br>CPU: Intel i7-1370PRE 14C/20T, vPro, 1.9GHz, 28/20W cTDP;<br>Graphics: Intel® Iris® Xe 96 EUs; 2x DP/HDMI; 1x eDP;<br>Ethernet: 2x Intel i226-IT Gbit, TSN; HD audio; TPM 2.0;<br>2x SATA, 1x USB4, 4x USB3, 8x USB2, PCIe Gen 4 2x4, PCIe Gen 3 8x;<br>32GB LPDDR5-6400 memory;<br>-40...+85°C, recommended for 24/7 operation. | MSC HMM-<br>RLP-1370PRE-5N031I<br>PCBFTX         | OR |
| 122144    | COM-HPC Mini module (95mm x 70mm);<br>CPU: Intel i7-1370PRE 14C/20T, vPro, 1.9GHz, 28/20W cTDP;<br>Graphics: Intel® Iris® Xe 96 EUs; 2x DP/HDMI; 1x eDP;<br>Ethernet: 2x Intel i226-IT Gbit, TSN; HD audio; TPM 2.0;<br>2x SATA, 1x USB4, 4x USB3, 8x USB2, PCIe Gen 4 2x4, PCIe Gen 3 8x;<br>16GB LPDDR5-6400 memory;<br>-40...+85°C, recommended for 24/7 operation. | MSC HMM-<br>RLP-1370PRE-4N031I<br>PCBFTX         | PV |
| 120727    | COM-HPC Mini module (95mm x 70mm);<br>CPU: Intel i5-1350PRE 12C/16T, vPro, 1.8GHz, 28/20W cTDP;<br>Graphics: Intel® Iris® Xe 80 EUs; 2x DP/HDMI; 1x eDP;<br>Ethernet: 2x Intel i226-IT Gbit, TSN; HD audio; TPM 2.0;<br>2x SATA, 1x USB4, 4x USB3, 8x USB2, PCIe Gen 4 2x4, PCIe Gen 3 8x;<br>16GB LPDDR5-6400 memory;<br>-40...+85°C, recommended for 24/7 operation. | MSC<br>HMM-<br>RLP-1350PRE-4N031I<br>PCBFTX      | OR |
| 120729    | COM-HPC Mini module (95mm x 70mm);<br>CPU: Intel i3-1315URE 6C/8T, 1.2GHz, 15/12W cTDP;<br>Graphics: Intel® UHD 64 EUs; 2x DP/HDMI; 1x eDP;<br>Ethernet: 2x Intel i226-IT Gbit, TSN; HD audio; TPM 2.0;<br>2x SATA, 1x USB4, 4x USB3, 8x USB2, PCIe Gen 4 2x4, PCIe Gen 3 8x;<br>8GB LPDDR5-5200 memory;<br>-40...+85°C, recommended for 24/7 operation.               | MSC<br>HMM-<br>RLP-1315URE-3N031I<br>PCBFTX      | PV |
| 120731    | COM-HPC Mini module (95mm x 70mm);<br>CPU: Intel i5-1345UE 10C/12T, vPro, 1.4GHz, 15/12W cTDP;<br>Graphics: Intel® Iris® Xe 80 EUs; 2x DP/HDMI; 1x eDP;<br>Ethernet: 2x Intel i226-LM Gbit, TSN; HD audio; TPM 2.0;<br>2x SATA, 1x USB4, 4x USB3, 8x USB2, PCIe Gen 4 2x4, PCIe Gen 3 8x;<br>16GB LPDDR5-6400 memory;<br>0...+60°C.                                    | MSC HMM-<br>RLP-1345UE-4N031C<br>PCBFTX          | OR |
| 120733    | COM-HPC Mini module (95mm x 70mm);<br>CPU: Intel i3-1315UE 6C/8T, 1.2GHz, 15/12W cTDP;<br>Graphics: Intel® UHD 64 EUs; 2x DP/HDMI; 1x eDP;<br>Ethernet: 2x Intel i226-LM Gbit, TSN; HD audio; TPM 2.0;<br>2x SATA, 1x USB4, 4x USB3, 8x USB2, PCIe Gen 4 2x4, PCIe Gen 3 8x;<br>16GB LPDDR5-5200 memory;<br>0...+60°C.                                                 | MSC HMM-<br>RLP-1315UE-4N031C<br>PCBFTX          | PV |
| 120735    | COM-HPC Mini module (95mm x 70mm);<br>CPU: Intel Processor U300E 5C/6T, 1.1GHz, 15/12W cTDP;<br>Graphics: Intel® UHD 48 EUs; 2x DP/HDMI; 1x eDP;<br>Ethernet: 2x Intel i226-LM Gbit, TSN; HD audio; TPM 2.0;<br>2x SATA, 1x USB4, 4x USB3, 8x USB2, PCIe Gen 4 2x4, PCIe Gen 3 8x;<br>8GB LPDDR5-5200 memory;<br>0...+60°C.                                            | MSC HMM-RLP-<br>U300UE-3N031C<br>PCBFTX          | PV |

Ordering Information for TRIA HMM-RLP \*PV = Preferred variant; OR = on Request (in OEM quantities only)

## Accessories

### Carrier Boards

| Order No. | Description                | Reference           |
|-----------|----------------------------|---------------------|
| 121630    | COM-HPC Mini Carrier Board | MSC HM-MB-EV BRDFTX |

Carrier Options for TRIA COM-HPC Mini modules

### Cooling Solutions

| Order No. | Description                           | Reference                 |
|-----------|---------------------------------------|---------------------------|
| 116871    | Fan kit for Heatsink HMM-RLP PWM fan. | MSC HMM-FANKIT-01 HSF-001 |

Fan Kit for COM-HPC Mini Heatsinks

| Order No. | Description                                                                                                                                                                                                 | Reference              |
|-----------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------|
| 116849    | Passive heatsink for HMM-RLP consisting of a single-piece aluminum profile with fins, standoffs without thread (2.7mm inner diameter), screws and thermopads for the thermal contact to CPU, chipset, NVMe. | MSC HMM-RLP-01 HSI-001 |
| 116850    | Heatspreader for HMM-RLP. Single-piece aluminum profile, standoffs without thread (2.7mm inner diameter), screws and thermopads for the thermal contact to CPU, chipset, NVMe.                              | MSC HMM-RLP-01 HSP-001 |
| 116851    | Heatspreader for HMM-RLP. Single-piece aluminum profile, standoffs with M2.5 thread, screws and thermopads for the thermal contact to CPU, chipset, NVMe.                                                   | MSC HMM-RLP-02 HSP-001 |

Cooling Options for TRIA HMM-RLP

Tria Technologies GmbH  
Industriestr. 16  
76297 Stutensee  
[info@tria-technologies.com](mailto:info@tria-technologies.com)  
[tria-technologies.com](http://tria-technologies.com)

Copyright © 2024 Tria Technologies GmbH. All data is for information purposes only and is subject to change without notice. No guarantee for legal purposes is implied. Information in this document has been carefully checked, however, no responsibility for inaccuracies has to be assumed. All brand or product names may be trademarks and property of their respective owners.