


TRIA Q7-BT

Intel® System on Chip (SOC) Atom™ E3800

70 x 70 mm

4.5 to 12 W (typ.)

-40 +85



Q S E V E N



Highlights

- Intel® Atom™ System-On-Chip with Quad-/ Dual- /Single-Core Processor:
 - E3845 Quad-Core, 1.91 GHz, 10W TDP
 - E3827 Dual-Core, 1.75 GHz, 8W TDP
 - E3826 Dual-Core, 1.46 GHz, 7W TDP
 - E3825 Dual-Core, 1.33 GHz, 6W TDP
 - E3815 Single-Core, 1.46 GHz, 5W TDP
 - E3805 Dual-Core, 1.33 GHz, 3W TDP
- Up to 4GB DDR3L SDRAM (opt. ECC)
- Up to 32GB eMMC Flash (optional)
- 2x SATA-II interfaces (1 used for opt. Flash Disk)
- Integrated Intel Gen. 7 HD Graphics
- DisplayPort 1.1a up to 2560×1600, HDMI up to 1920×1200
- Dual-Channel LVDS 24 or 18 bit up to 1920×1200
- Dual Simultaneous Display support
- Gigabit Ethernet
- 3x PCIe x1 Gen. 2.0 ports
- USB 3.0 Host, optional USB 3.0 Device
- Up to 6x USB 2.0 Host, optional USB 2.0 Device
- UART, LPC, HD Audio, SPI, I2C, SMBus, SDIO, opt. TPM

Technical Data

Technology	x86
Formfactor	Qseven
CPU	Intel® Atom™ E3845, E3827, E3826, E3825, E3815, E3805
Chipset	in SOC
RAM	up to 4 GB LVDDR3-1333 SDRAM, soldered optional ECC
Flash	optional on-board SATA Flash Disk up to 64 GB optional in-board eMMC Flash up to 32GB
Storage Interfaces	2x SATA 3Gb/s one optionally used for SATA Flash Disk
USB	1x USB 3.0 Host up to 6x USB Host optional USB 3.0 Device optional USB 2.0 Device
Serial Interfaces	I ² C Bus SMBus SPI Bus
Bus Interfaces	3x PCI-Express x1 Gen. 2 LPC Bus
Display Controller	Integrated Intel HD Graphics Gen. 7
Display Memory	UMA
Display Interfaces	HDMI up to 1920 x 1200 @60Hz DisplayPort 1.1a up to 2560 x 1600 @60Hz LVDS 18/24 bit, dual channel, up to 1920 x 1200 @60Hz
Network Interface	10/100/1000Base-TX
Audio Interface	HD Audio (I2S optional)
Security Device	TPM 1.2 optional
Miscellaneous	Watchdog Timer: Initiates system reset, (programmable, 1s ... 255h) Fan Supply: PWM Speed Control for system fan on carrier board RTC battery: external System Monitoring: Voltage, Temperature, CPU Fan, System Fan
Feature Highlights	ECC controlled Memory Optional TPM for Security HDMI, DisplayPort outputs
Firmware	AMI Aptio UEFI
OS Support	Windows 7 / ES7 / 8 / 10 Linux EAPI (HW Programming Interface)
Power Requirement	+5V +/-5%, 5V Standby optional

Environment	Operating Temperature: 0° ... 60°C (operating, commercial) -40° ... 85°C (operating, industrial) -20° ... 85°C (storage, commercial) -40° ... 85°C (storage, industrial) Humidity: 5 ... 95% (operating, non-condensing), 5 ... 95% (storage, non-condensing)
Dimensions	70mmx70mm
Certificates	UL / CE
Cooling	Heatspreader with threaded standoffs Heatsink with threaded standoffs
Carrier	Qseven Rev. 2.0 Carrier board in 3.5" (ECX) form factor Carrier board for evaluation in ATX form factor

Technical Data for TRIA Q7-BT

Order Reference

Order No.	Description	Reference	Status*
65993	Qseven 2.0 module with Intel Atom E3815 SC 1.46GHz, 5W TDP, 1 GB DDR3L, GbE LAN, USB 3.0 Host, 6x USB 2.0 Host, UART, std. temp.	MSC Q7-BT-15-1001 PCBFTX	PV
65995	Qseven 2.0 module with Intel Atom E3815 SC 1.46GHz, 5W TDP, 2 GB DDR3L, GbE LAN, USB 3.0 Host, USB 3.0 Device, 3x USB 2.0 Host, USB 2.0 Host/Device, UART, std. temp.	MSC Q7-BT-15-2008 PCBFTX	OR
82310	Qseven 2.0 module with Intel Atom E3815 SC 1.46GHz, 5W TDP, 2GB DDR3L, 16GB eMMC Flash, GbE LAN, USB 3.0 Host, 5x USB 2.0, USB 2.0 Host/Device, UART, TPM, ind. temp.	MSC Q7-BT-15-2402I PCBFTX	PV
48938	Qseven 2.0 module with Intel Atom E3815 SC 1.46GHz, 5W TDP, 2 GB DDR3L, 4 GB eMMC Flash, GbE LAN, USB 3.0 Host, 6x USB 2.0 Host, UART, ind. temp.	MSC Q7-BT-15-2201I PCBFTX	PV
48924	Qseven 2.0 module with Intel Atom E3825 DC 1.33GHz, 6 W TDP, 2 GB DDR3L, 4 GB eMMC Flash, GbE LAN, USB 3.0 Host, 6x USB 2.0 Host, UART, ind. temp.	MSC Q7-BT-25-2201I PCBFTX	PV
48925	Qseven 2.0 module with Intel Atom E3826 DC 1.46GHz, 7 W TDP, 2 GB DDR3L, 4 GB eMMC Flash, GbE LAN, USB 3.0 Host, 6x USB 2.0 Host, UART, ind. temp.	MSC Q7-BT-26-2201I PCBFTX	PV
82312	Qseven 2.0 module with Intel Atom E3826 DC 1.46GHz, 7W TDP, 4GB DDR3L, 16GB eMMC Flash, GbE LAN, USB 3.0 Host, 5x USB 2.0, USB 2.0 Host/Device, UART, TPM, ind. temp.	MSC Q7-BT-26-4402I PCBFTX	PV
65495	Qseven 2.0 module with Intel Atom E3827 DC 1.75GHz, 8 W TDP, 2 GB DDR3L, 4 GB eMMC Flash, GbE LAN, USB 3.0 Host, 6x USB 2.0 Host, UART, ind. temp.	MSC Q7-BT-27-2201I PCBFTX	PV
66172	Qseven 2.0 module with Intel Atom E3845 QC 1.91GHz, 10 W TDP, 2 GB DDR3L, GbE LAN, USB 3.0 Host, 4x USB 2.0 Host, UART, ind. temp.	MSC Q7-BT-45-2006I PCBFTX	PV
48927	Qseven 2.0 module with Intel Atom E3845 QC 1.91GHz, 10 W TDP, 2 GB DDR3L, 4 GB eMMC Flash, GbE LAN, USB 3.0 Host, 6x USB 2.0 Host, UART, TPM, ind. temp.	MSC Q7-BT-45-2200I PCBFTX	PV
48991	Qseven 2.0 module with Intel Atom E3845 QC 1.91GHz, 10 W TDP, 4 GB DDR3L, GbE LAN, USB 3.0 Host, 6x USB 2.0 Host, UART, ind. temp.	MSC Q7-BT-45-4001I PCBFTX	PV
82316	Qseven 2.0 module with Intel Atom E3845 QC 1.91GHz, 10W TDP, 4GB DDR3L, 16GB eMMC Flash, GbE LAN, USB 3.0 Host, 5x USB 2.0, USB 2.0 Host/Device, UART, TPM, ind. temp.	MSC Q7-BT-45-4402I PCBFTX	PV
48929	Qseven 2.0 module with Intel Atom E3845 QC 1.91GHz, 10W TDP, 4GB DDR3L, ECC, GbE LAN, USB 3.0 Host, USB 3.0 Device, 3x USB 2.0, USB 2.0 Host/Device, UART, ind. temp.	MSC Q7-BT-45-8005I PCBFTX	OR
67047	Qseven 2.0 module with Intel Atom E3815 SC 1.46GHz, 5W TDP, 2GB DDR3L, 4GB SATA Flash, GbE LAN, USB 3.0 Host, 5x USB 2.0, USB 2.0 Host/Device, UART, TPM, ind. temp.	MSC Q7-BT-15-20B2I PCBFTX	PV
69460	Qseven 2.0 module with Intel Atom E3805 DC 1.33GHz, 3W TDP, 2GB DDR3L, 16GB eMMC Flash, GbE LAN, USB 3.0 Host, 5x USB 2.0, USB 2.0 Host/Device, UART, TPM, ind. temp. -- Processor & Module without any Graphics!	MSC Q7-BT-05-2402I PCBFTX	PV
69353	Qseven 2.0 module with Intel Atom E3815 SC 1.46GHz, 5W TDP, 2GB DDR3L, 8GB eMMC Flash, GbE LAN, USB 3.0 Host, 6x USB 2.0, UART, std. temp.	MSC Q7-BT-15-2301 PCBFTX	PV
67758	Qseven 2.0 module with Intel Atom E3826 DC 1.46GHz, 7W TDP, 2GB DDR3L, 8GB eMMC Flash, GbE LAN, USB 3.0 Host, 6x USB 2.0, UART, std. temp.	MSC Q7-BT-26-2301 PCBFTX	OR

Order No.	Description	Reference	Status*
82314	Qseven 2.0 module with Intel Atom E3827 DC 1.75GHz, 8W TDP, 4GB DDR3L, 32GB eMMC Flash, GbE LAN, USB 3.0 Host, 6x USB 2.0, UART, ind. temp.	MSC Q7-BT-27-4501I PCBFTX	OR
65316	Qseven 2.0 module with Intel Atom E3845 QC 1.91GHz, 10W TDP, 4GB DDR3L, 4GB eMMC Flash, GbE LAN, USB 3.0 Host, 5x USB 2.0, USB 2.0 Host/Device, UART, TPM, embedded DisplayPort Output (eDP), no LVDS, ind. temp.	MSC Q7-BT-45-4207I PCBFTX	OR
71625	Qseven 2.0 module with Intel Atom E3845 QC 1.91GHz, 10W TDP, 2GB DDR3L, 8GB eMMC Flash, GbE LAN, USB 3.0 Host, 6x USB 2.0, UART, ind. temp.	MSC Q7-BT-45-2301I PCBFTX	OR
71623	Qseven 2.0 module with Intel Atom E3845 QC 1.91GHz, 10W TDP, 4GB DDR3L, 4GB eMMC Flash, GbE LAN, USB 3.0 Host, 6x USB 2.0, UART, ind. temp.	MSC Q7-BT-45-4201I PCBFTX	OR
73499	Qseven 2.0 module with Intel Atom E3815 SC 1.46GHz, 5W TDP, 2GB DDR3L, GbE LAN, USB 3.0 Host, 6x USB 2.0, UART, ind. temp.	MSC Q7-BT-15-2001I PCBFTX	OR

Ordering Information for TRIA Q7-BT

*PV = Preferred variant; OR = on Request (in OEM quantities only)

Accessories

Carrier Options

Order No.	Description	Reference
67690	Qseven Rev. 2.0 compatible embedded platform (148 x 102mm), 10-28V input voltage, 1x RS232 on DB9 connector, 1x RS485 on pin header, 1x RS232 no handshake on pin header, dual RJ45 LAN connector with LED, 1x SATA, 1x mSATA slot, SD card holder, 1x USB 3.0 connector, 2x USB 2.0 connector, 1x USB 2.0 on pin row, 1x microUSB 2.0 OTG, CAN, I2C, LPC/ GPIO on pin header, I2C/SMBus, SPI, DisplayPort connector, LVDS/eDP on JLI30 connector, regulated backlight supply, mini PCI Express slot, HD Audio, CMOS battery. Commercial temperature range 0..+70°C	MSC Q7-MB-EP6-601 PCBFTX

Carrier Options for TRIA Q7-EL/AL/BT/BW

Cooling Options

Unable to render include or excerpt-include. Could not retrieve page.

Starter Kits

Unable to render include or excerpt-include. Could not retrieve page.

Tria Technologies GmbH
Industriestr. 16
76297 Stutensee
info@tria-technologies.com
tria-technologies.com

Copyright © 2024 Tria Technologies GmbH. All data is for information purposes only and is subject to change without notice. No guarantee for legal purposes is implied. Information in this document has been carefully checked, however, no responsibility for inaccuracies has to be assumed. All brand or product names may be trademarks and property of their respective owners.