

TRIA Q7-IMX6PLUS

NXP™ i.MX6 ARM® Cortex™-A9



70 x 70 mm

4-6 W

40 +85



Highlights

- NXP™ i.MX 6 ARM® Cortex™-A9 Solo, DualLite, Dual, Quad, DualPlus and QuadPlus processor
- MPEG-4 Video Encoding/Decoding 1080p
- HDMI graphics 1920 x 1080 x 30fps
- Dual-channel LVDS 1920 x 1080 x 30fps
- Up to 4GB DDR3L SDRAM
- Up to 64GB eMMC Flash
- Gigabit Ethernet Interface
- 1x PCI Express x1
- 1x SATA-II (3Gbps, quad-/dual-core only)
- 1x USB Device/Host + up to 4x USB 2.0
- 1x MMC/SD/SDIO Interface
- CAN Interface
- I2S Audio Interface
- MIPI CSI-2 Camera Interface (optional)
- Micro SD Card Socket

Technical Data

Technology	ARM
Formfactor	Qseven 2.0
CPU	<p>NXP™ i.MX 6 ARM® Cortex™-A9:</p> <ul style="list-style-type: none"> • i.MX 6QuadPlus, quad-core, 800MHz...1.2GHz • i.MX 6Quad, quad-core, 800MHz...1.2GHz • i.MX 6DualPlus, dual-core, 800MHz...1.2GHz • i.MX 6Dual, dual-core, 800MHz...1.2GHz • i.MX 6DualLite, dual-core, 800MHz...1.0GHz • i.MX 6Solo, single-core, 800MHz...1.0GHz
Chipset	SOC
RAM	Up to 4GB DDR3L SDRAM (DDR-1066), soldered
Flash	Up to 64GB eMMC Flash (optional) or Up to 1GB SLC NAND Flash (optional)
Storage Interfaces	Micro SD Card Socket (optional) 1x MMC/SD/SDIO 1x SATA-II (3Gbps, not supported by Solo/DualLite CPU)
USB	1x USB 2.0 Host/Client, 1x USB 2.0 Host or 1x USB 2.0 Host/Client, 4x USB 2.0 Host (optional)
Serial Interfaces	UART
Bus Interfaces	1x PCI Express x1 1x CAN 2.0B 1x I2C up to 400 Kbit/s 1x SPI (with two chip selects) 1x SMBus
Display Controller	Video, 2D and 3D Graphics Units integrated in i.MX6 Processor OpenGL® ES 1.1/2.0/Halti, OpenVG™ 1.1, OpenCL™ 1.1 EP Multi-Format Hardware Video Encoder/Decoder
Display Interfaces	Dual-channel LVDS interface, 18 or 24 bit (up to 1920x1080). Also usable as 2x single-channel LVDS interface (up to 1366x768) HDMI V1.4 up to WUXGA (1920x1080) incl. Full-HD @ 30fps MIPI CSI-2 Camera Interface (optional, Feature Connector)
Network Interface	1x 10/100/1000BASE-T Ethernet
Audio Interface	I2S Audio
Miscellaneous	Watchdog Timer for system reset (programmable, 1s ... 600s) 8x GPIO, configurable as input or output 2kbit ID EEPROM on SMBus
Feature Highlights	FEATURE HIGHLIGHTS DATA HERE!
OS Support	Linux Board Support Package
Power Requirement	Power Supply +5V +/-5%, 5V Standby Power Consumption 4-6 W typ. (depending on CPU and optional features)
Environment	Temperature Range: 0°C ... +70°C operating commercial -40°C ... +85°C operating extended -40°C ... +85°C storage Humidity: 5 ... 95% (operating, non condensing) 5 ... 95% (storage, non-condensing)

Dimensions	70 x 70 x 13 mm with heat spreader installed
Certificates	UL / CE

Technical Data for TRIA Q7-IMX6PLUS

Order Reference

Order No.	Description	Reference	Status*
66762	Qseven module based on NXP i.MX6S Single-Core Cortex-A9 processor at 800MHz, 1GB DDR3 soldered, integrated Graphics, HDMI max. 1920x1080, dual-channel LVDS, Ethernet controller (10/100/1000Base-T), 512MB NAND Flash, micro SD socket, no SATA, 1x PCIe, 1x USB2.0 Host, 1x USB2.0 Host/Client, I2S Audio; industrial temperature -40...+85°C	MSC Q7-IMX6PLUS-111 PCBFTX	PV
66764	Qseven module based on NXP i.MX6S Single-Core Cortex-A9 processor at 800MHz, 1GB DDR3 soldered, integrated Graphics, HDMI max. 1920x1080, dual-channel LVDS, Ethernet controller (10/100/1000Base-T), 4GB eMMC Flash, micro SD socket, no SATA, 1x PCIe, 4x USB2.0 Host, 1x USB2.0 Host/Client, I2S Audio; industrial temperature -40...+85°C	MSC Q7-IMX6PLUS-112 PCBFTX	PV
66710	Qseven module based on NXP i.MX6D Dual-Core Cortex-A9 processor at 800MHz, 2GB DDR3 soldered, integrated Graphics, HDMI max. 1920x1080, dual-channel LVDS, Ethernet controller (10/100/1000Base-T), 4GB eMMC Flash, micro SD socket, 1x SATA, 1x PCIe, 4x USB2.0 Host, 1x USB2.0 Host/Client, I2S Audio; industrial temperature -40...+85°C	MSC Q7-IMX6PLUS-123 PCBFTX	PV
67693	Qseven module based on NXP i.MX 6DualPlus Dual-Core Cortex-A9 processor at 800MHz, 2GB DDR3 soldered, integrated Graphics, HDMI max. 1920x1080, dual-channel LVDS, Ethernet controller (10/100/1000Base-T), 4GB eMMC Flash, micro SD socket, 1x SATA, 1x PCIe, 4x USB2.0 Host, 1x USB2.0 Host/Client, I2S Audio; industrial temperature -40...+85°C	MSC Q7-IMX6PLUS-163 PCBFTX	PV
66766	Qseven module based on NXP i.MX6DL Dual-Lite Cortex-A9 processor at 800MHz, 2GB DDR3 soldered, integrated Graphics, HDMI max. 1920x1080, dual-channel LVDS, Ethernet controller (10/100/1000Base-T), 4GB eMMC Flash, micro SD socket, no SATA, 1x PCIe, 4x USB2.0 Host, 1x USB2.0 Host/Client, I2S Audio; industrial temperature -40...+85°C	MSC Q7-IMX6PLUS-133 PCBFTX	PV
66768	Qseven module based on NXP i.MX6Q Quad-Core Cortex-A9 processor at 800MHz, 2GB DDR3 soldered, integrated Graphics, HDMI max. 1920x1080, dual-channel LVDS, Ethernet controller (10/100/1000Base-T), 4GB eMMC Flash, micro SD socket, 1x SATA, 1x PCIe, 4x USB2.0 Host, 1x USB2.0 Host/Client, I2S Audio; industrial temperature -40...+85°C	MSC Q7-IMX6PLUS-143 PCBFTX	PV
67692	Qseven module based on NXP i.MX 6QuadPlus Quad-Core Cortex-A9 processor at 800MHz, 2GB DDR3 soldered, integrated Graphics, HDMI max. 1920x1080, dual-channel LVDS, Ethernet controller (10/100/1000Base-T), 4GB eMMC Flash, micro SD socket, 1x SATA, 1x PCIe, 4x USB2.0 Host, 1x USB2.0 Host/Client, I2S Audio; industrial temperature -40...+85°C	MSC Q7-IMX6PLUS-183 PCBFTX	PV
69932	Qseven module based on NXP i.MX 6QuadPlus Quad-Core Cortex-A9 processor at 1GHz, 2GB DDR3 soldered, integrated Graphics, HDMI max. 1920x1080, dual-channel LVDS, Ethernet controller (10/100/1000Base-T), 4GB eMMC Flash, micro SD socket, 1x SATA, 1x PCIe, 4x USB2.0 Host, 1x USB2.0 Host/Client, I2S Audio; commercial temperature 0...70°C	MSC Q7-IMX6PLUS-083 PCBFTX	OR

Ordering Information for TRIA Q7-IMX6PLUS

*PV = Preferred variant; OR = on Request (in OEM quantities only)

Accessories

Carrier Options

Order No.	Description	Reference
39698	Power supply Unit with connector for Q7-MB-EPx baseboards. Provides 12V and 5V power. Does not include power cable from wall to PSU, please order optionally 40188 (US) or 35512 (EU). Optionally 35513 is a suitable combined SATA data and power cable.	MSC Q7-MB-EP-PSU1
40824	Qseven embedded platform (148 x 102 mm), 10-28V input voltage, 1x RS232 on pin row, 1x RS232 debug port, dual RJ45 LAN connector with LED, 1x SATA, 1x mSATA con., SD card holder, 2x external USB, 1x USB Host/Client, 1 intern USB, I2C, SMBus, SPI, DVI + LVDS, touch screen support, regulated backlight supply, mini PCI Express socket, AC97 Audio codec, Audio on pin row, CMOS battery, system fan support. Extended temperature range -20..+85°C	MSC Q7-MB-EP4-001 PCBFTX

Carrier Options for TRIA Q7-IMX6PLUS

Cooling Options

Order No.	Description	Reference
1128531	Heatspreader with unthreaded distance bolts for Q7-IMX6Plus module with flip-chip processor package (all single-core & dual-lite versions, all standard temperature versions)	MSC Q7-IMX6-03 HSP-001
1128532	Heatspreader with unthreaded distance bolts for Q7-IMX6Plus module with lidded processor package (extended temperature versions of dual- and quad-core only)	MSC Q7-IMX6-03 HSP-002
1053769	Heat rail for Q7 baseboards. Recommended for conductive heat transfer from the Q7 module to the Q7 baseboard. Already assembled on all MSC baseboards.	MSC Q7-XXX-01 HTR-001

Cooling Options for TRIA Q7-IMX6PLUS

Other Accessories

Order No.	Description	Reference
40402	Debug Console (UART) Adapter for i.MX6-based Qseven and nanoRISC modules, with 8-pin FFC cable to connect COM module to 9-pin D-Sub connector	MSC Debug Console Adapter
67822	Debug Adapter for i.MX6-based Qseven, SMARC and nanoRISC modules, with 8-pin FFC cable to connect to COM module, adapter provides headers for JTAG connection to Lauterbach and/or Goepel debuggers	MSC JTAG Adapter FFC 8-pin

Other Accessories for TRIA Q7-IMX6PLUS

Starter Kits

Order No.	Description	Reference
43885	Starterkit for TRIA Q7-IMX6(PLUS) modules. Includes TRIA Q7-MB-EP4-001 Baseboard, Heatspreader, Console Adapter, SD Card with Linux OS installation and Power Supply. Does not include TRIA Q7-IMX6(PLUS) module. Please order your choice of TRIA Q7-IMX6(PLUS)-xyz PCBFTX separately.	MSC Q7-SK-IMX6-EP4-KIT001 SETPAC

Starter Kits for TRIA Q7-IMX6PLUS

Tria Technologies GmbH
Industriestr. 16
76297 Stutensee
info@tria-technologies.com
tria-technologies.com

Copyright © 2024 Tria Technologies GmbH. All data is for information purposes only and is subject to change without notice. No guarantee for legal purposes is implied. Information in this document has been carefully checked, however, no responsibility for inaccuracies has to be assumed. All brand or product names may be trademarks and property of their respective owners.