

## TRIA SM2S-G2L

Renesas RZ/G2L Arm® Cortex®-A55/M33



82 x 50 mm

4-6 W

-40 +85 °C



### Highlights

- Single or Dual core Arm Cortex-A55 Microprocessor at 1.2GHz
- Arm Cortex-M33 Real Time Processor at 200MHz
- Arm Mali™-G31 multimedia 2D/3D Graphics Processing Unit (GPU)
- H.264 Video Encoding and Decoding (VPU)
- Up to 2GB DDR4 SDRAM with inline ECC
- Up to 256GB eMMC Flash
- Dual-channel LVDS
- MIPI CSI-2 Camera interface
- Up to 4x USB 2.0 Host interfaces
- 1x USB 2.0 Host/Device interface
- Dual Gigabit Ethernet
- Wireless Module (optional)
- MMC/SD/SDIO interface (optional)
- 2x CAN-FD interfaces
- 2x I2S Audio interfaces
- 14x GPIO
- UART, SPI, I2C
- SMARC 2.1.1 Compliant

## Technical Data

<b>Technology</b>	ARM
<b>Formfactor</b>	SMARC™ Short Size
<b>CPU</b>	<p>Renesas RZ/G2L family</p> <ul style="list-style-type: none"> <li>• Single Core Arm Cortex-A55 at 1.2GHz, secure</li> <li>• Single Core Arm Cortex-A55 at 1.2GHz, non-secure</li> <li>• Dual Core Arm Cortex-A55 at 1.2GHz, secure</li> <li>• Dual Core Arm Cortex-A55 at 1.2GHz, non-secure</li> </ul> <p>Arm Cortex-M33 Real Time Processor at 200MHz</p>
<b>Chipset</b>	SOC
<b>RAM</b>	Up to 2GB 1600MT/s DDR4 SDRAM, soldered, inline ECC support
<b>Flash</b>	Up to 256GB eMMC Flash
<b>Storage Interfaces</b>	1x MMC/SD/SDIO (optional, SDIO and WIFI/BT are mutual exclusive)
<b>USB</b>	1x USB 2.0 Host/Client, 4x USB 2.0 Host or 1x USB 2.0 Host/Client, 1x USB 2.0 Host (optional)
<b>Serial Interfaces</b>	2x UART with Tx/D, Rx/D, RTS, CTS 2x UART with Tx/D, Rx/D only
<b>Bus Interfaces</b>	4x I2C up to 400 Kbit/s 2x SPI (with two chip selects) 2x CAN-FD
<b>Display Controller</b>	<p>Arm Mali-G31 multimedia 2D/3D Graphics Processing Unit (GPU) OpenGL ES1.1, 2.0, 3.0, 3.1 and 3.2 support OpenCL 2.0 Full Profile support Video Codec Processor with H.264 support</p>
<b>Display Interfaces</b>	Dual-channel LVDS interface, 18 or 24 bit (up to 1920x1080); also usable as one single-channel LVDS interface (up to 1366x768) or MIPI-DSI Display Interface, 4 lanes, up to 1920x1080 @ 60fps (optional)
<b>Network Interface</b>	<p>2x 10/100/1000BASE-T Ethernet Wireless Module with 802.11b/g/n and Bluetooth 5.0, single band 2.4GHz, soldered (optional, SDIO and WIFI/BT are mutual exclusive)</p>
<b>Audio Interface</b>	2x I2S Audio
<b>Security Device</b>	<p>Advanced Security, Safety, and Reliability integrated in the SOC Trusted Platform Module (TPM) 2.0 (optional)</p>
<b>Miscellaneous</b>	<p>Watchdog Timer for system reset (programmable, 1s ... 600s) RTC / temperature compensated (optional) 14x GPIO, configurable as input or output, interrupt capable 64kbit ID EEPROM on I2C bus MIPI CSI-2 camera interface (CSI0, 2 lane) or MIPI CSI-2 camera interface (CSI1, 4-lane)</p>
<b>Feature Highlights</b>	SMARC 2.1.1 compatible
<b>Firmware</b>	uboot
<b>OS Support</b>	<p>Linux Board Support Package Android Board Support Package (on request)</p>

<b>Power Requirement</b>	Power Main: +5V +/-5% Power Standby: +5V +/-5% Power Consumption 4-6 W typ. (depending on CPU and optional features)
<b>Environment</b>	Temperature Range: Commercial: 0°C ... 70°C (operating) -20°C ... 85°C (storage) Extended: -25°C ... 85°C (operating) -40°C ... 85°C (storage) Industrial: -40°C ... 85°C (operating) -40°C ... 85°C (storage)  Humidity: 5 ... 95% (operating, non-condensing) 5 ... 95% (storage, non-condensing)
<b>Dimensions</b>	82 x 50 mm
<b>Certificates</b>	UL / CE
<b>Cooling</b>	Heatspreader Heatsink
<b>Carrier</b>	TRIA SM2-MB-EP1 TRIA SM2S-MB-EP5

Technical Data for TRIA SM2S-G2L

## Order Reference

Order No.	Description	Reference	Status*
113810	SMARC module based on Renesas RZ/G2L Dual-Core Cortex-A55 processor at 1.2GHz (secure version), 2GB DDR4, 32GB eMMC Flash, 1x GbE LAN, 1x USB2.0 Host, 1x USB2.0 Host/Device, 2x CAN, SDIO, LVDS, MIPI CSI-2 Camera input (CSI0, 2 lane); industrial temperature -40...+85°C	MSC SM2S-G2L-DC-15N0270I PCBFTX	PV
113811	SMARC module based on Renesas RZ/G2L Dual-Core Cortex-A55 processor at 1.2GHz, 2GB DDR4, 16GB eMMC Flash, 2x GbE LAN, 1x USB2.0 Host, 1x USB2.0 Host/Device, 2x CAN, SDIO, LVDS, MIPI CSI-2 Camera input (CSI0, 2 lane); industrial temperature -40...+85°C	MSC SM2S-G2L-DCN-14N02B0I PCBFTX	PV
113852	SMARC module based on Renesas RZ/G2L Single-Core Cortex-A55 processor at 1.2GHz, 1GB DDR4, 16GB eMMC Flash, 1x GbE LAN, 1x USB2.0 Host, 1x USB2.0 Host/Device, 2x CAN, SDIO, LVDS, MIPI CSI-2 Camera input (CSI0, 2 lane); industrial temperature -40...+85°C	MSC SM2S-G2L-SCN-04N0270I PCBFTX	PV

Ordering Information for TRIA SM2S-G2L

\*PV = Preferred variant; OR = on Request (in OEM quantities only)

## Accessories

### Carrier Options

Order No.	Description	Reference
68488	SMARC 2.0 Embedded Platform with PCI Express x4 slot, GbE, SATA, USB 3.0, USB 2.0, USB 2.0 OTG, RS232, CAN, SPI, eSPI, SMBus, I2C and GPIO interface, LVDS/eDP, DisplayPort and HDMI display interface, regulated backlight supply, HD/I2S audio interface, MIPI CSI-2 camera interface, mini PCI Express card slot, SD card slot, fan connector, CMOS battery, Mini-ITX form factor (170 x 170 mm), ATX power connector and single 12V/24V power jack, commercial temperature range 0..+70°C	MSC SM2-MB-EP1-001 PCBFTX
83977	SMARC 2.1 compatible embedded platform (146 x 80mm), 10-36V input voltage, 3x RS232, 2x CAN, dual RJ45 LAN with LED (1 x LAN i210) , 1x M.2 2280 Key M slot, mPCIe slot, 1x USB 3.0 Type A, 1x USB 2.0 Type A, 1x USB 2.0 internal, 1x µUSB 2.0 Host/Device, 2x SPI, I <sup>2</sup> C, 8 GPIO on FC, 1x HDMI, LVDS/eDP/DSI on JLI30 connector, µSD Card Slot, regulated backlight supply, I2S Audio, 1W Mono, camera connector, RTC battery. Industrial temperature range -40..+85°C, ARM full version	MSC SM2S-MB-EP5-002 PCBFTX
83981	SMARC 2.1 compatible embedded platform (146 x 80mm), 10-36V input voltage, 2x UART, 1x RS232, 2x CAN, 1x RJ45 LAN with LED, 1x USB 2.0 Type A, 1x USB3.0 Type A, 1x USB 2.0 internal, 1x µUSB 2.0 Host/Device, 2x SPI, 12 GPIO on FC, 1x HDMI , µSD Card Slot, LVDS/eDP/DSI on JLI30 connector, regulated backlight supply, RTC battery. Industrial temperature range -40..+85°C, ARM slim version	MSC SM2S-MB-EP5-004 PCBFTX

Carrier Options TRIA SM2S-IMX8MLC/IMX95/IMX91/V2L/G2L/IMX93/G2UL/AM62X/IMX8/IMX8M/IMX8PLUS/IMX8MINI/IMX8NANO/IMX6/IMX6ULL

### Cooling Options

Order No.	Description	Reference
110192	Heatspreader for SM2S-G2L and SM2S-V2L module, consisting of a single-piece aluminum plane and thermal pad for contact to the processor, with 2.7mm through-hole standoffs	MSC SM2S-X2L-01 HSP-001

Cooling Options TRIA SM2S-V2L/G2L

### Other Accessories

Order No.	Description	Reference
82479	Debug Console (UART) Adapter for i.MX6-based Qseven and nanoRISC modules, with 8-pin FFC cable to connect COM module to 9-pin D-Sub connector	MSC Debug Console Adapter
68948	Debug Adapter for i.MX6-based Qseven, SMARC and nanoRISC modules, with 10-pin FFC cable to connect to COM module, adapter provides headers for JTAG connection to Lauterbach and/ or Goepel debuggers	MSC JTAG Adapter FFC 10-pin

Other Accessories TRIA SM2S-IMX8MLC/IMX95/IMX91/V2L/G2L/IMX93/G2UL/AM62X/IMX8/IMX8PLUS

Tria Technologies GmbH  
Industriestr. 16  
76297 Stutensee  
info@tria-technologies.com  
tria-technologies.com

Copyright © 2024 Tria Technologies GmbH. All data is for information purposes only and is subject to change without notice. No guarantee for legal purposes is implied. Information in this document has been carefully checked, however, no responsibility for inaccuracies has to be assumed. All brand or product names may be trademarks and property of their respective owners.